

1. IDENTIFICATION OF THE MIXTURE AND OF THE SUPPLIER
Product Identifier

Product	Industrial Nitrocellulose Top Coat Black [32-0002]
Recommended use of chemical	Use as coating
Restriction on use	No open flames, No sparks, and No smoking

Supplier's details

Company	Big-Ben Chemical Company Limited
Address	168 Mu 2 Donkhaidee Krathumban Samutsakorn 74110 Thailand
Telephone number	+66 2 811 1442 or +66 2 811 1443
Fax number	+66 2 811 0632
E-mail	bbp@bbp.co.th
Emergency phone number	+66 2 811 1442 or + 66 2 811 1443

2. HAZARD IDENTIFICATION

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CSR 1910.1200; the SDS and labels contain all the information as required by the standard.

Flammable liquids	Category 1
Acute toxicity - oral	Category 5
Acute toxicity - dermal	Category 1
Skin corrosion/irritation	Category 2
Eye damage/irritation	Category 2A
Toxic to reproduction	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Hazardous to the aquatic environment - acute hazard	Category 2

Remark:

Percentage of mixture consisting of ingredient(s) of unknown oral toxicity: 48.01%

Percentage of mixture consisting of ingredient(s) of unknown dermal toxicity: 52.21%

Percentage of mixture consisting of ingredient(s) of unknown inhalation toxicity: 49.74%

GHS label elements

Pictogram or symbol



Signal word

Danger

Hazard statement:

- H224 Extremely flammable liquid and vapour
- H303 May be harmful if swallowed
- H310 Fatal in contact with skin
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H361 Suspected of damaging fertility or the unborn child
- H373 May cause damage to organs through prolonged or repeated exposure
- H401 Toxic to aquatic life

Precautionary statement

[PREVENTION]

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat / sparks / open flames / hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground / bond container and receiving equipment.
- P241 Use explosion-proof electrical / ventilating / lighting / equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust / fume / gas / mist / vapors / spray.
- P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
- P262 Do not get in eyes, on skin, or on clothing.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / protective clothing / eye protection / face protection.

[RESPONSE]

- P302+P350 IF ON SKIN Gently wash with plenty of soap and water.
- P302+P352 IF ON SKIN Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair) Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
- P304+P340 IF INHALED Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned Get medical advice / attention.
- P310 Immediately call a POISON CENTER or doctor / physician.
- P312 Call a POISON CENTER or doctor / physician if you feel unwell.
- P314 Get medical advice / attention if you feel unwell.
- P321 Specific treatment (see on this label).
- P322 Specific measures (see on this label).
- P332+P313 IF skin irritation occurs Get medical advice / attention.
- P337+P313 IF eye irritation persists Get medical advice / attention.
- P361 Remove / Take off immediately all contaminated clothing.
- P362 Take off contaminated clothing and wash before reuse.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire Use dry sand, dry chemical or alcohol-resistant foam for extinction.

[STORAGE]

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

[DISPOSAL]

- P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Content % (w/w)
1,2,4-Trimethyl Benzene	95-63-6	1.30 - 1.51
1-ACETOXY-2-ETHOXYETHANE	111-15-9	5.92 - 6.86
2-BUTOXYETHANOL	111-76-2	3.95 - 4.57
2-PROPANOL	67-63-0	1.78 - 2.06
Acetone	67-64-1	3.95 - 4.57
Butyl Acetate	123-86-4	17.76 - 20.57
Carbon Black	1333-86-4	2.17 - 2.51
Cellulose nitrate	9004-70-1	4.15 - 4.80

Ethyl acetate	141-78-6	1.97 - 2.29
PETROLEUM ETHER	64742-82-1	4.87 - 5.63
Polymer resin	-	24.96 - 28.90
Toluene	108-88-3	3.95 - 4.57
Xylene	1330-20-7	18.28 - 21.16

4. FIRST AID MEASURES

Inhalation	Remove to fresh air. If unconscious, place in recovery position and seek medical attention immediately.
Skin contact	Immediately flush with water for at least 15 minutes. Remove contaminated clothing. Seek medical attention immediately. Wash thoroughly after handling.
Eye contact	Hold eyelids apart and immediately flush with plenty of water for 15 minutes. Seek medical advice. Remove contact lenses.
Ingestion	Rinse mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.
Most important symptoms/effects, acute and delayed	Dizziness. Drowsiness. Headache. Nausea. Vomiting. Weakness. Unconsciousness. Skin and eye redness. Pain. Nausea. Vomiting.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media	Dry chemical. Carbon Dioxide (CO ₂). Alcohol-resistant foam. Water spray.
Unsuitable extinguishing media	High volume water jet.
Specific hazards arising from the chemical	Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Container may rupture on heating.
Specific protective equipment and precautions for firefighters	Wear self-contained breathing apparatus and full protective clothing for firefighting.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures	Keep unnecessary personnel away. Prevent further leakage or spillage if safe to do so. Use personal protective equipment. Use only non-sparking tools.
Environmental precautions	Prevent the material from entering drains or water courses.
Methods and materials for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations.

7. HANDLING AND STORAGE

Precautions for safe handling	Avoid breathing vapor and contact with eyes, skin, and clothing. Do not leave containers open. Avoid repeated or prolonged contact with skin.
Conditions for safe storage, including any incompatibilities	Keep away from heat or flames. Keep in cool, dry, ventilated storage and in closed containers. Store away from oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters	<u>1-ACETOXY-2-ETHOXYETHANE</u> OSHA PEL-TWA 100 ⁴⁷ Skin notification Y ⁴⁷ NIOSH REL-TWA 0.5 ⁴⁷ Skin notification Y ⁴⁷ ACGIH TLV-TWA 5 ⁴⁷ Skin notification Y ⁴⁷ CAL/OSHA PEL-TWA 5 ⁴⁷ Skin notification Y ⁴⁷ Safe Work Australia (Australia, 4/2024)
--------------------	--

TWA : 2 ppm 8 hours. ¹⁶
TWA : 10.9 mg/m³ 8 hours. ¹⁶

2-BUTOXYETHANOL
OSHA

PEL-TWA 50⁴⁸
Skin notification Y⁴⁸
NIOSH
REL-TWA 5⁴⁸
Skin notification Y⁴⁸
ACGIH
TLV-TWA 20⁴⁸
Skin notification N⁴⁸

CAL/OSHA
PEL-TWA 20⁴⁸
Skin notification Y⁴⁸
Safe Work Australia (Australia, 4/2024)
TWA : 10 ppm 8 hours. ¹⁶
TWA : 49 mg/m³ 8 hours. ¹⁶
STEL : 40 ppm 15 minutes. ¹⁶
STEL : 196 mg/m³ 15 minutes. ¹⁶

2-PROPANOL
OSHA

PEL-TWA 400⁴⁹
Skin notification N⁴⁹
NIOSH
REL-TWA 400⁴⁹
REL-STEL 500⁴⁹
Skin notification N⁴⁹
ACGIH
TLV-TWA 200⁴⁹
TLV-STEL 400⁴⁹

Safe Work Australia (Australia, 4/2024)
TWA : 200 ppm 8 hours. ¹⁶
TWA : 491 mg/m³ 8 hours. ¹⁶
STEL : 400 ppm 15 minutes. ¹⁶
STEL : 984 mg/m³ 15 minutes. ¹⁶

Acetone
OSHA

PEL-TWA 1000⁵⁰
Skin notification N⁵⁰
NIOSH
REL-TWA 250⁵⁰
Skin notification N⁵⁰
ACGIH
TLV-TWA 2500⁵⁰
TLV-STEL 500⁵⁰
Skin notification N⁵⁰
CAL/OSHA
PEL-TWA 500⁵⁰
PEL-STEL 750⁵⁰
PEL-C 3000⁵⁰

Skin notification N⁵⁰
Safe Work Australia (Australia, 4/2024)
TWA : 250 ppm 8 hours. ¹⁶
TWA : 583 mg/m³ 8 hours. ¹⁶

TWA : 594 mg/m³ 8 hours. ¹⁵
 STEL : 500 ppm 15 minutes. ¹⁶
 STEL : 1187 mg/m³ 15 minutes. ¹⁶

Butyl Acetate

OSHA

PEL-TWA 150⁵¹

Skin notification N⁵¹

NIOSH

REL-TWA 150⁵¹

REL-STEL 200⁵¹

Skin notification N⁵¹

ACGIH

TLV-TWA 50⁵¹

TLV-STEL 150⁵¹

Skin notification N

CAL/OSHA

PEL-TWA 150⁵¹

PEL-STEL 200⁵¹

Skin notification N⁵¹

Safe Work Australia (Australia, 4/2024)

TWA : 50 ppm 8 hours. ¹⁶

TWA : 270 mg/m³ 8 hours. ¹⁶

STEL : 100 ppm 15 minutes. ¹⁶

STEL : 541 mg/m³ 15 minutes. ¹⁶

Carbon Black

OSHA

PEL-TWA 3.5 mg/m³⁵²

NIOSH

REL-TWA 3.5 mg/m³⁵²

CAL/OSHA

PEL-TWA 3.5 mg/m³⁵²

Safe Work Australia (Australia, 4/2024)

TWA : 3 mg/m³ 8 hours. ¹⁶

Ethyl acetate

OSHA

PEL-TWA 400⁵³

Skin notification N⁵³

NIOSH

REL-TWA 400⁵³

Skin notification N⁵³

ACGIH

TLV-TWA 400⁵³

Skin notification N⁵³

CAL/OSHA

PEL-TWA 400⁵³

Skin notification N⁵³

Safe Work Australia (Australia, 4/2024)

TWA : 200 ppm 8 hours. ¹⁶

TWA : 720 mg/m³ 8 hours. ¹⁶

STEL : 400 ppm 15 minutes. ¹⁶

STEL : 1440 mg/m³ 15 minutes. ¹⁶

Safe Work Australia (Australia, 4/2024)

TWA : 50 ppm 8 hours. ¹⁷

TWA : 296 mg/m³ 8 hours. ¹⁷

STEL : 100 ppm 15 minutes. ¹⁷

STEL : 593 mg/m³ 15 minutes. ¹⁷

STEL : 593 mg/m³ 15 minutes. ¹⁷

Toluene

OSHA

PEL-TWA 200 ppm⁵⁴

PEL-C 300 ppm; 500 ppm (Peak) [10 min maximum in an 8 hr shift]⁵⁴

Skin notification N⁵⁴

NIOSH

REL-TWA 100 ppm (375 mg/m³)⁵⁴

REL-STEL 150 ppm (560 mg/m³)⁵⁴

Skin notification N⁵⁴

ACGIH

TLV-TWA 20 ppm [2006]⁵⁴

Skin notification N⁵⁴

CAL/OSHA

PEL-TWA 10 ppm (37 mg/m³)⁵⁴

PEL-STEL 150 ppm (560 mg/m³)⁵⁴

PEL-C 500 ppm⁵⁴

Skin notification Y⁵⁴

Safe Work Australia (Australia, 4/2024)

TWA : 20 ppm 8 hours. ¹⁸

TWA : 75 mg/m³ 8 hours. ¹⁸

Xylene

OSHA

PEL-TWA 100¹⁵

Skin notification N¹⁵

NIOSH

REL-TWA 100¹⁵

Skin notification N¹⁵

ACGIH

TLV-TWA 100¹⁵

TLV-STEL 150¹⁵

Skin notification N¹⁵

CAL/OSHA

PEL-TWA 100¹⁵

PEL-STEL 150¹⁵

PEL-C 300¹⁵

Skin notification N¹⁵

Safe Work Australia (Australia, 4/2024)

TWA : 80 ppm 8 hours. ¹⁸

TWA : 350 mg/m³ 8 hours. ¹⁸

STEL : 150 ppm 15 minutes. ¹⁸

STEL : 655 mg/m³ 15 minutes. ¹⁸

Appropriate engineering controls

Personal protective equipment

Respiratory protection

Hand protection

Eye protection

Skin and body protection

Organic vapor respirator

Rubber gloves. Neoprene.

Safety goggle.

Wear suitable clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state

Colour

Odour

Liquid

Black

Organic solvent

pH	Not available
Melting point/freezing point	Not available
Boiling point or initial boiling point and boiling range	-20.0 °C (-4.0 °F) (PETROLEUM ETHER)
Flash point	-40.0 °C (-40.0 °F) (PETROLEUM ETHER)
Flammability	Flammable
Lower and upper explosion limit/flammability limit	Not Available Not Available
Vapour pressure	1403 hPa at 20 °C (Ethyl acetate)
Density and/or relative density	0.89 - 0.99 g/cm ³
Relative vapour density	Not Available
Solubility	Soluble in Organic solvent
Partition coefficient n-octanol/water (log value)	Not applicable
Auto-ignition temperature	280.0 °C (536.0 °F) (PETROLEUM ETHER)
Decomposition temperature	Not applicable
Viscosity	85 - 95 KU at 30 °C
Particle characteristics	Not applicable

10. STABILITY AND REACTIVITY

Reactivity	Reacts violently with strong acids and strong oxidants
Chemical stability	Stable under normal storage and handling conditions
Possibility of hazardous reaction	Will not occur
Condition to avoid	High temperatures, sparks, open flame, and all other sources of ignition
Incompatible materials	Strong oxidizing agents, strong acids
Hazardous decomposition products	Not available

11. TOXICOLOGICAL INFORMATION

Acute toxicity (oral)	ATEmix = 3032.03 mg/kg (Category 5) 1,2,4-Trimethyl Benzene LD50 (rat) oral = 3280.00 mg/kg ¹⁹ 1-ACETOXY-2-ETHOXYETHANE LD50 (rat) oral = 2900.00 mg/kg ²⁰ 2-BUTOXYETHANOL LD50 (rat) oral = 470.00 mg/kg ²¹ 2-PROPANOL LD50 (rat) oral = 4710.00 mg/kg ²² Acetone LD50 (rat) oral = 5800.00 mg/kg ²³ Butyl Acetate LD50 (rat) oral = 10736.00 mg/kg ²⁴ Carbon Black LD50 (rat) oral = 10000.00 mg/kg ²⁵ Ethyl acetate LD50 (rat) oral = 11.00 mg/kg ²⁶ PETROLEUM ETHER LD50 (rat) oral = 5000.00 mg/kg ³ Toluene LD50 (rat) oral = 5000.00 mg/kg ²⁷
Acute toxicity (dermal)	ATEmix = 38.66 mg/kg (Category 1) 1,2,4-Trimethyl Benzene LD50 (rabbit) dermal = 3160.00 mg/kg ¹⁹ 1-ACETOXY-2-ETHOXYETHANE LD50 (rabbit) dermal = 10300.00 mg/kg ²⁰ 2-BUTOXYETHANOL LD50 (rabbit) dermal = 400.00 mg/kg ²¹ 2-PROPANOL LD50 (rabbit) dermal = 12870.00 mg/kg ²² Acetone LD50 (rabbit) dermal = 7426.00 mg/kg ²³ Butyl Acetate LD50 (rabbit) dermal = 16.00 mg/kg ²⁴ PETROLEUM ETHER LD50 (rabbit) dermal = 2000.00 mg/kg ³ Toluene LD50 (rabbit) dermal = 14100.00 mg/kg ²⁷
Acute toxicity (inhalation)	Not available
Skin corrosion and skin irritation	Causes skin irritation (1,2,4-Trimethyl Benzene, 2-BUTOXYETHANOL, Toluene, Xylene)
Serious eye damage or eye irritation	Causes serious eye irritation (1,2,4-Trimethyl Benzene, 2-BUTOXYETHANOL, 2-PROPANOL, Acetone, Ethyl acetate)

Respirator and skin sensitization	Not classified
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Suspected of damaging fertility or the unborn child (Toluene)
Specific target organ toxicity following single exposure	May cause respiratory irritation (1,2,4-Trimethyl Benzene,2-PROPANOL,Acetone,Butyl Acetate,Ethyl acetate,Toluene)
Specific target organ toxicity following repeated exposure	May cause damage to organs through prolonged or repeated exposure (PETROLEUM ETHER,Toluene)
Aspiration hazard	Not classified

12. ECOLOGICAL INFORMATION

Acute aquatic hazard	Toxic to aquatic life <u>1,2,4-Trimethyl Benzene</u> LC50 (fish) 96 hr = 7.72 mg/L²⁸ EC48 (shrimp) 48 hr = 3.60 mg/L²⁸ <u>1-ACETOXY-2-ETHOXYETHANE</u> LC50 (fish) 96 hr = 40 mg/L³⁵ <u>2-BUTOXYETHANOL</u> LC50 (fish) 96 hr = 1474 mg/L³⁶ EC48 (shrimp) 48 hr = 1500 mg/L³⁶ <u>2-PROPANOL</u> LC50 (fish) 96 hr = 6120 mg/L²² <u>Acetone</u> LC50 (fish) 96 hr = 4740 mg/L²³ <u>Butyl Acetate</u> LC50 (fish) 96 hr = 18 mg/L²⁴ EC48 (shrimp) 48 hr = 32 mg/L²⁴ <u>Carbon Black</u> LC50 (fish) 96 hr = 100 mg/L³⁷ <u>Ethyl acetate</u> LC50 (fish) 96 hr = 230 mg/L³¹ ErC-EC72 (Fungi) 96 hr = 5600 mg/L³¹ <u>Toluene</u> LC50 (fish) 96 hr = 7.3 mg/L³⁸ EC48 (shrimp) 48 hr = 6 mg/L³⁸ ErC-EC72 (Fungi) 96 hr = 12.5 mg/L³⁸ <u>Xylene</u> LC50 (fish) 96 hr = 3.30 mg/L⁵
Long term aquatic hazard	No information
Persistence and degradability	Rapidly degradable (Acetone,Butyl Acetate,Ethyl acetate,Toluene,Xylene)
Bioaccumulative potential	Bioaccumulative potential <u>1,2,4-Trimethyl Benzene</u> log KOW = 3.78²⁸ BCF = 31.275²⁸ <u>1-ACETOXY-2-ETHOXYETHANE</u> log KOW = 0.24⁴¹ BCF = 3⁴¹ <u>2-BUTOXYETHANOL</u> log KOW = 0.83⁴² BCF = 3⁴² <u>Acetone</u> log KOW = -0.24⁴³ BCF = 0.69⁴³ <u>Butyl Acetate</u> log KOW = 1.78⁴⁴ BCF = 7.00⁴⁴ <u>Ethyl acetate</u> log KOW = 0.73⁴⁵

BCF = 3⁴³

Toluene
log KOW = 2.73⁴⁶

BCF = 13⁴⁶

Xylene
log KOW = 3.20¹³

BCF = 14.80¹³

Mobility in soil

The product is insoluable in water. If released to water, some of the components will have tendency to evaporate while other components are expected to be highly mobile in soil and have the potential to reach underground water supplies.

Other adverse effects

Not available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Disposing of this material/container should be done under all the regulations or handled by authorized waste collector in your country

Container disposal

Do not re-use empty containers

14. TRANSPORT INFORMATION

Labels required



UN number

1263

UN proper shipping name

Paint

Transport hazard class(es)

3

Packing group

III

Environmental hazards

Not applicable

Special precautions

Not applicable

Transport in bulk

Not applicable

15. REGULATORY INFORMATION

Inventory of existing chemical substance produced or imported in USA (TSCA)

All component in this product are listed

Toxic substance control act (TSCA)

All component in this product are listed

16. OTHER INFORMATION

Issue date: 24 June 2025

References

1. <https://echa.europa.eu/brief-profile/-/briefprofile/100.002.270> (23-10-19)
2. <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~0KYTYa:3> (03-05-19)
3. <https://echa.europa.eu/brief-profile/-/briefprofile/100.059.242> (24-12-19)
4. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.267> (17-12-19)
5. <https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/682> (04-05-19)
6. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124> (24-12-19)
7. <https://echa.europa.eu/brief-profile/-/briefprofile/100.059.242> (14/8/19)
8. <https://echa.europa.eu/brief-profile/-/briefprofile/100.002.591> (03-05-19)
9. <https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/1574> (03-05-19)
10. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124> (04-05-19)
11. -
12. <https://pubchem.ncbi.nlm.nih.gov/compound/7292#section=Environmental-Abiotic-Degradation> (23-10-19)
13. <https://pubchem.ncbi.nlm.nih.gov/compound/7292#section=Environmental-Fate> (04-05-19)
14. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=13> (25-12-19)

15. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=228> (04-05-19)
16. Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (20-8-2024)
17. Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (20-8-24)
18. Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (21-8-2024)
19. <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~B0u97X:1> (3-5-19)
20. <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~m8awRK:3> (3-5-19)
21. <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~IQIQFd:1> (03-05-19)
22. <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~yPvzP0:1> (3-5-19)
23. <https://echa.europa.eu/brief-profile/-/briefprofile/100.000.602> (23-12-19)
24. <https://echa.europa.eu/brief-profile/-/briefprofile/100.004.236#ScientificProperties> (17-12-19)
25. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.191> (17-12-19)
26. <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~jnUXDq:3> (14/8/19)
27. <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~VMFBml:3> (3-5-19)
28. <https://echa.europa.eu/brief-profile/-/briefprofile/100.002.216> (3-5-19)
29. <https://echa.europa.eu/brief-profile/-/briefprofile/100.003.550> (03-05-19)
30. <https://echa.europa.eu/brief-profile/-/briefprofile/100.003.297> (3-5-19)
31. <https://echa.europa.eu/brief-profile/-/briefprofile/100.005.001> (14/8/19)
32. <https://monographs.iarc.who.int/list-of-classifications> (22-1-2025)
33. <https://echa.europa.eu/brief-profile/-/briefprofile/100.000.601> (3-5-19)
34. <https://echa.europa.eu/brief-profile/-/briefprofile/100.004.236> (04-05-19)
35. <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~7TG1XJ:1> (03-05-19)
36. <https://echa.europa.eu/brief-profile/-/briefprofile/100.003.550#ScientificProperties> (17-12-19)
37. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.191> (22-1-2025)
38. <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~IQhZ8l:1> (03-05-19)
39. <https://echa.europa.eu/brief-profile/-/briefprofile/100.003.297> (03-05-19)
40. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.191> (04-05-19)
41. <https://pubchem.ncbi.nlm.nih.gov/compound/8095#section=Environmental-Fate-Exposure-Summary> (03-05-19)
42. <https://pubchem.ncbi.nlm.nih.gov/compound/8133#section=Environmental-Abiotic-Degradation> (03-05-19)
43. <https://pubchem.ncbi.nlm.nih.gov/compound/180> (23-12-19)
44. <https://pubchem.ncbi.nlm.nih.gov/compound/31272#section=Environmental-Abiotic-Degradation> (04-05-19)
45. <https://pubchem.ncbi.nlm.nih.gov/compound/8857#section=Environmental-Abiotic-Degradation> (14/8/19)
46. <https://pubchem.ncbi.nlm.nih.gov/compound/1140#section=Environmental-Fate> (03-05-19)
47. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=122> (3-5-19)
48. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=130> (03-05-19)
49. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=475> (3-5-19)
50. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=476> (23-12-19)
51. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=178> (17-12-19)
52. <https://www.osha.gov/chemicaldata/236> (22-1-2025)
53. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=263> (14/8/19)
54. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=89> (03-05-19)