

1. IDENTIFICATION OF THE MIXTURE AND OF THE SUPPLIER
Product Identifier

Product	Automotive Enamel White [37-5001]
Recommended use of chemical	Use as coating
Restriction on use	No open flames, No sparks, and No smoking

Supplier's details

Company	Big-Ben Chemical Company Limited
Address	168 Mu 2 Donkhaidee Krathumban Samutsakorn 74110 Thailand
Telephone number	+66 2 811 1442 or +66 2 811 1443
Fax number	+66 2 811 0632
E-mail	bbp@bbp.co.th
Emergency phone number	+66 2 811 1442 or + 66 2 811 1443

2. HAZARD IDENTIFICATION

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CSR 1910.1200; the SDS and labels contain all the information as required by the standard.

Flammable liquids	Category 2
Acute toxicity - dermal	Category 4
Skin corrosion/irritation	Category 3
Eye damage/irritation	Category 2A
Sensitization - skin	Category 1
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1
Hazardous to the aquatic environment - acute hazard	Category 2
Hazardous to the aquatic environment - long-term hazard	Category 3

Remark:

Percentage of mixture consisting of ingredient(s) of unknown oral toxicity: 35.49%

Percentage of mixture consisting of ingredient(s) of unknown dermal toxicity: 71.22%

Percentage of mixture consisting of ingredient(s) of unknown inhalation toxicity: 89.05%

GHS label elements

Pictogram or symbol



Signal word

Danger

Hazard statement:

- H225 Highly Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H312 Harmful in contact with skin
- H316 Causes mild skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H372 Causes damage to organs through prolonged or repeated exposure
- H401 Toxic to aquatic life
- H412 Harmful to aquatic life with long lasting effects

Precautionary statement

[PREVENTION]

P210 Keep away from heat / sparks / open flames / hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground / bond container and receiving equipment.
P241 Use explosion-proof electrical / ventilating / lighting / equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust / fume / gas / mist / vapors / spray.
P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves / protective clothing / eye protection / face protection.

[RESPONSE]

P301+P310 IF SWALLOWED Immediately call a POISON CENTER or doctor / physician.
P302+P352 IF ON SKIN Wash with plenty of soap and water.
P303+P361+P353 IF ON SKIN (or hair) Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
P305+P351+P338 IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor / physician if you feel unwell.
P314 Get medical advice / attention if you feel unwell.
P321 Specific treatment (see on this label).
P322 Specific measures (see on this label).
P331 Do NOT induce vomiting.
P332+P313 IF skin irritation occurs Get medical advice / attention.
P333+P313 IF skin irritation or rash occurs Get medical advice / attention.
P337+P313 IF eye irritation persists Get medical advice / attention.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire Use dry sand, dry chemical or alcohol-resistant foam for extinction.

[STORAGE]

P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

[DISPOSAL]

P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Content % (w/w)
Butanoxime	96-29-7	1.47 - 1.70
Ethyl Benzene	100-41-4	1.01 - 1.17
PETROLEUM ETHER	64742-82-1	23.92 - 27.70
Polymer resin	-	28.20 - 32.65
Titanium Dioxide	13463-67-7	33.92 - 39.27
Xylene	1330-20-7	6.49 - 7.52

4. FIRST AID MEASURES

Inhalation	Remove to fresh air. If unconscious, place in recovery position and seek medical attention immediately.
Skin contact	Immediately flush with water for at least 15 minutes. Remove contaminated clothing. Seek medical attention immediately. Wash thoroughly after handling.
Eye contact	Hold eyelids apart and immediately flush with plenty of water for 15 minutes. Seek medical advice. Remove contact lenses.
Ingestion	Rinse mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

Most important symptoms/effects, acute and delayed	Dizziness. Drowsiness. Headache. Nausea. Vomitting. Weakness. Unconsciousness. Skin and eye redness. Pain. Nausea. Vomitting.
--	---

5. FIRE FIGHTING MEASURES

Suitable extinguishing media	Dry chemical. Carbon Dioxide (CO ₂). Alcohol-resistant foam. Water spray.
Unsuitable extinguishing media	High volume water jet.
Specific hazards arising from the chemical	Flammable liquid. Vapors can form an ignitable misture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Container may rupture on heating.
Specific protective equipment and precautions for firefighters	Wear self-contained breathing apparatus and full protective clothing for firefighting.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures	Keep unnecessary personnel away. Prevent further leakage or spillage if safe to do so. Use personal protective equipment. Use only non-sparkling tools.
Environmental precautions	Prevent the material from entering drains or water courses.
Methods and materials for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations.

7. HANDLING AND STORAGE

Precautions for safe handling	Avoid breathing vapor and contact with eyes, skin, and clothing. Do no leave containers open. Avoid repeated or prolonged contact with skin.
Conditions for safe storage, including any incompatibilites	Keep away from heat or flames. Keep in cool, dry, ventilated storage and in closed containers. Store away from oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters	<u>Ethyl Benzene</u> OSHA PEL-TWA 100 ²⁴ Skin notification N ²⁴ NIOSH REL-TWA 100 ²⁴ REL-STEL 125 ²⁴ Skin notification N ²⁴ ACGIH TLV-TWA 20 ²⁴ Skin notification N ²⁴ CAL/OSHA PEL-TWA 100 ²⁴ PEL-STEL 125 ²⁴ Skin notification N ²⁴ Safe Work Australia (Australia, 4/2024) TWA : 20 ppm 8 hours. ¹⁸ TWA : 87 mg/m ³ 8 hours. ¹⁸ Safe Work Australia (Australia, 4/2024) TWA : 50 ppm 8 hours. ¹⁶ TWA : 296 mg/m ³ 8 hours. ¹⁶ STEL : 100 ppm 15 minutes. ¹⁶ STEL : 593 mg/m ³ 15 minutes. ¹⁶ <u>Titanium Dioxide</u> OSHA PEL-TWA 15 ²⁵ Skin notification N ²⁵ NIOSH Skin notification N ²⁵ ACGIH
--------------------	---

TLV-TWA 10²⁵
 Skin notification N²⁵
 CAL/OSHA
 PEL-TWA 10²⁵
 Skin notification N²⁵
 Safe Work Australia (Australia, 4/2024)
 TWA : 10 mg/m³ 8 hours. ¹⁷
Xylene
 OSHA
 PEL-TWA 100¹⁵
 Skin notification N¹⁵
 NIOSH
 REL-TWA 100¹⁵
 Skin notification N¹⁵
 ACGIH
 TLV-TWA 100¹⁵
 TLV-STEL 150¹⁵
 Skin notification N¹⁵
 CAL/OSHA
 PEL-TWA 100¹⁵
 PEL-STEL 150¹⁵
 PEL-C 300¹⁵
 Skin notification N¹⁵
 Safe Work Australia (Australia, 4/2024)
 TWA : 80 ppm 8 hours. ¹⁷
 TWA : 350 mg/m³ 8 hours. ¹⁷
 STEL : 150 ppm 15 minutes. ¹⁷
 STEL : 655 mg/m³ 15 minutes. ¹⁷
 Provide adequate ventilation. Install local exhaust.

Appropriate engineering controls

Personal protective equipment

Respiratory protection	Organic vapor respirator
Hand protection	Rubber gloves. Neoprene.
Eye protection	Safety goggle.
Skin and body protection	Wear suitable clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	High Viscosity liquid
Colour	White
Odour	Organic solvent
pH	Not available
Melting point/freezing point	Not available
Boiling point or initial boiling point and boiling range	139.5 °C (283.1 °F) (Xylene)
Flash point	18.0 °C (64.4 °F) (Xylene)
Flammability	Flammable
Lower and upper explosion limit/flammability limit	Not available
Vapour pressure	9 hPa at 20 °C (Ethyl Benzene)
Density and/or relative density	1.1 - 1.2 g/cm ³
Relative vapour density	Not available
Solubility	Soluble in Organic solvent
Partition coefficient n-octanol/water (log	Not applicable

value)

Auto-ignition temperature	187.5 °C (369.5 °F) (Xylene)
Decomposition temperature	Not applicable
Viscosity	85 - 90 KU at 30 °C
Particle characteristics	Not applicable

10. STABILITY AND REACTIVITY

Reactivity	Reacts violently with strong acids and strong oxidants
Chemical stability	Stable under normal storage and handling conditions
Possibility of hazardous reaction	Will not occur
Condition to avoid	High temperatures, sparks, open flame, and all other sources of ignition
Incompatible materials	Strong oxidizing agents, strong acids
Hazardous decomposition products	Not available

11. TOXICOLOGICAL INFORMATION

Acute toxicity (oral)	ATEmix = 5975.81 mg/kg (Not classified) Butanoxime LD50 (rat) oral = 900.00 mg/kg ¹ Ethyl Benzene LD50 (rat) oral = 3500.00 mg/kg ¹⁹ PETROLEUM ETHER LD50 (rat) oral = 5000.00 mg/kg ³ Titanium Dioxide LD50 (rat) oral = 10000.00 mg/kg ²⁰
Acute toxicity (dermal)	ATEmix = 1890.79 mg/kg (Category 4) Butanoxime LD50 (rabbit) dermal = 1000.00 mg/kg ¹ PETROLEUM ETHER LD50 (rabbit) dermal = 2000.00 mg/kg ³
Acute toxicity (inhalation)	Not available
Skin corrosion and skin irritation	Causes mild skin irritation (Xylene)
Serious eye damage or eye irritation	Causes serious eye irritation (Butanoxime)
Respirator and skin sensitization	Not classified
Skin sensitization	May cause an allergic skin reaction (Butanoxime)
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity following single exposure	Not classified
Specific target organ toxicity following repeated exposure	Causes damage to organs through prolonged or repeated exposure (Ethyl Benzene,PETROLEUM ETHER)
Aspiration hazard	May be fatal if swallowed and enters airways (Ethyl Benzene,PETROLEUM ETHER)

12. ECOLOGICAL INFORMATION

Acute aquatic hazard	Toxic to aquatic life <u>Butanoxime</u> LC50 (fish) 96 hr = 100 mg/L ¹ EC48 (shrimp) 48 hr = 201 mg/L ¹ ErC-EC72 (Fungi) 96 hr = 6.09 mg/L ¹ <u>Ethyl Benzene</u> LC50 (fish) 96 hr = 4.20 mg/L ²² EC48 (shrimp) 48 hr = 2.10 mg/L ²¹ ErC-EC72 (Fungi) 96 hr = 4.60 mg/L ²¹ <u>Titanium Dioxide</u> EC48 (shrimp) 48 hr = 100 mg/L ²⁰ ErC-EC72 (Fungi) 96 hr = 35.9 mg/L ²⁰ <u>Xylene</u> LC50 (fish) 96 hr = 3.30 mg/L ⁴
Long term aquatic hazard	Harmful to aquatic life with long lasting effects <u>Butanoxime</u> NOEC fish = 50 mg/L ¹

NOEC shrimp = 100 mg/L¹

NOEC fungi = 2.56 mg/L¹

Ethyl Benzene

NOEC fish = 3.30 mg/L²¹

NOEC shrimp = 1 mg/L²¹

NOEC fungi = 3.4 mg/L²¹

Titanium Dioxide

NOEC shrimp = 1.72 mg/L²³

NOEC fungi = 1 mg/L²³

Xylene

NOEC fish = 1.30 mg/L⁹

NOEC shrimp = 1.57 mg/L⁵

NOEC fungi = 0.44 mg/L⁵

Persistence and degradability

Rapidly degradable (Butanoxime, Ethyl Benzene, Xylene)

Bioaccumulative potential

Bioaccumulative potential

Butanoxime

log KOW = 0.63¹²

BCF = 0.5¹²

Ethyl Benzene

log KOW = 3.03²¹

BCF = 110²¹

Xylene

log KOW = 3.20¹³

BCF = 14.80¹³

Mobility in soil

The product is insoluble in water. If released to water, some of the components will have tendency to evaporate while other components are expected to be highly mobile in soil and have the potential to reach underground water supplies.

Other adverse effects

Not available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Disposing of this material/container should be done under all the regulations or handled by authorized waste collector in your country

Container disposal

Do not re-use empty containers

14. TRANSPORT INFORMATION

Labels required



UN number

1263

UN proper shipping name

Paint

Transport hazard class(es)

3

Packing group

III

Environmental hazards

Not applicable

Special precautions

Not applicable

Transport in bulk

Not applicable

15. REGULATORY INFORMATION

Inventory of existing chemical substance produced or imported in USA (TSCA)

All component in this product are listed

Toxic substance control act (TSCA)

All component in this product are listed

16. OTHER INFORMATION

Issue date: 19 June 2025

References

1. <https://echa.europa.eu/brief-profile/-/briefprofile/100.002.270> (23-10-19)
2. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.191> (17-12-19)
3. <https://echa.europa.eu/brief-profile/-/briefprofile/100.059.242> (24-12-19)
4. <https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/682> (04-05-19)
5. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124> (24-12-19)
6. <https://echa.europa.eu/brief-profile/-/briefprofile/100.059.242> (14/8/19)
7. <https://monographs.iarc.who.int/list-of-classifications> (22-1-2025)
8. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.191> (22-1-2025)
9. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124> (04-05-19)
10. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.191> (04-05-19)
11. -
12. <https://pubchem.ncbi.nlm.nih.gov/compound/7292#section=Environmental-Abiotic-Degradation> (23-10-19)
13. <https://pubchem.ncbi.nlm.nih.gov/compound/7292#section=Environmental-Fate> (04-05-19)
14. <https://www.osha.gov/chemicaldata/236> (22-1-2025)
15. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=228> (04-05-19)
16. Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (20-8-24)
17. Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (21-8-2024)
18. Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (20-8-2024)
19. <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~0KYTYa:3> (03-05-19)
20. <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~Q1zAvm:3> (3-5-19)
21. <https://echa.europa.eu/brief-profile/-/briefprofile/100.002.591> (03-05-19)
22. <https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/1574> (03-05-19)
23. <https://echa.europa.eu/brief-profile/-/briefprofile/100.033.327> (3-5-19)
24. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=13> (25-12-19)
25. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=246> (3-5-19)