

## 1. IDENTIFICATION OF THE MIXTURE AND OF THE SUPPLIER

### Product Identifier

Product	Automotive Enamel Lemon Yellow #581 [37-6014]
Recommended use of chemical	Use as coating
Restriction on use	No open flames, No sparks, and No smoking

### Supplier's details

Company	Big-Ben Chemical Company Limited
Address	168 Mu 2 Donkhaidee Krathumban Samutsakorn 74110 Thailand
Telephone number	+66 2 811 1442 or +66 2 811 1443
Fax number	+66 2 811 0632
E-mail	bbp@bbp.co.th
Emergency phone number	+66 2 811 1442 or + 66 2 811 1443

## 2. HAZARD IDENTIFICATION

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CSR 1910.1200; the SDS and labels contain all the information as required by the standard.

Flammable liquids	Category 1
Acute toxicity - oral	Category 5
Acute toxicity - dermal	Category 4
Skin corrosion/irritation	Category 2
Eye damage/irritation	Category 2A
Sensitization - skin	Category 1
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1
Hazardous to the aquatic environment - acute hazard	Category 2
Hazardous to the aquatic environment - long-term hazard	Category 1

Remark:

Percentage of mixture consisting of ingredient(s) of unknown oral toxicity: 51.48%

Percentage of mixture consisting of ingredient(s) of unknown dermal toxicity: 66.59%

Percentage of mixture consisting of ingredient(s) of unknown inhalation toxicity: 80.56%

### GHS label elements

Pictogram or symbol



Signal word

**Danger**

### Hazard statement:

- H224 Extremely flammable liquid and vapour
- H303 May be harmful if swallowed
- H304 May be fatal if swallowed and enters airways
- H312 Harmful in contact with skin
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H372 Causes damage to organs through prolonged or repeated exposure
- H401 Toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects

**Precautionary statement**
**[PREVENTION]**

- P210 Keep away from heat / sparks / open flames / hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground / bond container and receiving equipment.
- P241 Use explosion-proof electrical / ventilating / lighting / equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust / fume / gas / mist / vapors / spray.
- P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / protective clothing / eye protection / face protection.

**[RESPONSE]**

- P301+P310 IF SWALLOWED Immediately call a POISON CENTER or doctor / physician.
- P302+P352 IF ON SKIN Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair) Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
- P305+P351+P338 IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER or doctor / physician if you feel unwell.
- P314 Get medical advice / attention if you feel unwell.
- P321 Specific treatment (see on this label).
- P322 Specific measures (see on this label).
- P331 Do NOT induce vomiting.
- P332+P313 IF skin irritation occurs Get medical advice / attention.
- P333+P313 IF skin irritation or rash occurs Get medical advice / attention.
- P337+P313 IF eye irritation persists Get medical advice / attention.
- P362 Take off contaminated clothing and wash before reuse.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire Use dry sand, dry chemical or alcohol-resistant foam for extinction.
- P391 Collect spillage.

**[STORAGE]**

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

**[DISPOSAL]**

- P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

**3. COMPOSITION AND INFORMATION ON INGREDIENTS**

Chemical name	CAS No.	Content % (w/w)
Butanoxime	96-29-7	2.72 - 3.15
Ethyl Benzene	100-41-4	1.38 - 1.59
PETROLEUM ETHER	64742-82-1	24.94 - 28.88
Polymer resin	-	41.25 - 47.76
Xylene	1330-20-7	10.81 - 12.52
lead(2+) ion dioxochromiumbis(olate)	1344-37-2	13.91 - 16.10

**4. FIRST AID MEASURES**

Inhalation	Remove to fresh air. If unconscious, place in recovery position and seek medical attention immediately.
Skin contact	Immediately flush with water for at least 15 minutes. Remove contaminated clothing. Seek medical attention immediately. Wash thoroughly after handling.

Eye contact	Hold eyelids apart and immediately flush with plenty of water for 15 minutes. Seek medical advice. Remove contact lenses.
Ingestion	Rinse mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.
Most important symptoms/effects, acute and delayed	Dizziness. Drowsiness. Headache. Nausea. Vomiting. Weakness. Unconsciousness. Skin and eye redness. Pain. Nausea. Vomiting.

#### 5. FIRE FIGHTING MEASURES

Suitable extinguishing media	Dry chemical. Carbon Dioxide (CO <sub>2</sub> ). Alcohol-resistant foam. Water spray.
Unsuitable extinguishing media	High volume water jet.
Specific hazards arising from the chemical	Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Container may rupture on heating.
Specific protective equipment and precautions for firefighters	Wear self-contained breathing apparatus and full protective clothing for firefighting.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures	Keep unnecessary personnel away. Prevent further leakage or spillage if safe to do so. Use personal protective equipment. Use only non-sparking tools.
Environmental precautions	Prevent the material from entering drains or water courses.
Methods and materials for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations.

#### 7. HANDLING AND STORAGE

Precautions for safe handling	Avoid breathing vapor and contact with eyes, skin, and clothing. Do not leave containers open. Avoid repeated or prolonged contact with skin.
Conditions for safe storage, including any incompatibilities	Keep away from heat or flames. Keep in cool, dry, ventilated storage and in closed containers. Store away from oxidizing agent.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters	<u>Ethyl Benzene</u> OSHA PEL-TWA 100 <sup>14</sup> Skin notification N <sup>14</sup> NIOSH REL-TWA 100 <sup>14</sup> REL-STEL 125 <sup>14</sup> Skin notification N <sup>14</sup> ACGIH TLV-TWA 20 <sup>14</sup> Skin notification N <sup>14</sup> CAL/OSHA PEL-TWA 100 <sup>14</sup> PEL-STEL 125 <sup>14</sup> Skin notification N <sup>14</sup> Safe Work Australia (Australia, 4/2024) TWA : 20 ppm 8 hours. <sup>16</sup> TWA : 87 mg/m <sup>3</sup> 8 hours. <sup>16</sup> Safe Work Australia (Australia, 4/2024) TWA : 50 ppm 8 hours. <sup>17</sup> TWA : 296 mg/m <sup>3</sup> 8 hours. <sup>17</sup> STEL : 100 ppm 15 minutes. <sup>17</sup> STEL : 593 mg/m <sup>3</sup> 15 minutes. <sup>17</sup> <u>Xylene</u> OSHA PEL-TWA 100 <sup>15</sup>
--------------------	--

Skin notification N<sup>15</sup>  
 NIOSH  
 REL-TWA 100<sup>15</sup>  
 Skin notification N<sup>15</sup>  
 ACGIH  
 TLV-TWA 100<sup>15</sup>  
 TLV-STEL 150<sup>15</sup>  
 Skin notification N<sup>15</sup>  
 CAL/OSHA  
 PEL-TWA 100<sup>15</sup>  
 PEL-STEL 150<sup>15</sup>  
 PEL-C 300<sup>15</sup>  
 Skin notification N<sup>15</sup>  
 Safe Work Australia (Australia, 4/2024)  
 TWA : 80 ppm 8 hours. <sup>18</sup>  
 TWA : 350 mg/m<sup>3</sup> 8 hours. <sup>18</sup>  
 STEL : 150 ppm 15 minutes. <sup>18</sup>  
 STEL : 655 mg/m<sup>3</sup> 15 minutes. <sup>18</sup>  
 Provide adequate ventilation. Install local exhaust.

Appropriate engineering controls

## Personal protective equipment

Respiratory protection	Organic vapor respirator
Hand protection	Rubber gloves. Neoprene.
Eye protection	Safety goggle.
Skin and body protection	Wear suitable clothing

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid
Colour	Yellow
Odour	Organic solvent
pH	Not available
Melting point/freezing point	Not available
Boiling point or initial boiling point and boiling range	-20.0 °C (-4.0 °F) (PETROLEUM ETHER)
Flash point	-40.0 °C (-40.0 °F) (PETROLEUM ETHER)
Flammability	Flammable
Lower and upper explosion limit/flammability limit	Not available
Vapour pressure	9 hPa at 20 °C (Ethyl Benzene)
Density and/or relative density	0.95 - 1.05 g/cm <sup>3</sup>
Relative vapour density	Not available
Solubility	Soluble in Organic solvent
Partition coefficient n-octanol/water (log value)	Not applicable
Auto-ignition temperature	280.0 °C (536.0 °F) (PETROLEUM ETHER)
Decomposition temperature	Not applicable
Viscosity	80 - 90 KU at 30 °C
Particle characteristics	Not applicable

## 10. STABILITY AND REACTIVITY

Reactivity	Reacts violently with strong acids and strong oxidants
Chemical stability	Stable under normal storage and handling conditions
Possibility of hazardous reaction	Will not occur

Condition to avoid	High temperatures, sparks, open flame, and all other sources of ignition
Incompatible materials	Strong oxidizing agents, strong acids
Hazardous decomposition products	Not available

## 11. TOXICOLOGICAL INFORMATION

Acute toxicity (oral)	ATEmix = 4384.34 mg/kg (Category 5) Butanoxime LD50 (rat) oral = 900.00 mg/kg <sup>1</sup> Ethyl Benzene LD50 (rat) oral = 3500.00 mg/kg <sup>2</sup> PETROLEUM ETHER LD50 (rat) oral = 5000.00 mg/kg <sup>3</sup> lead(2+) ion dioxochromiumbis(olate) LD50 (rat) oral = 10000.00 mg/kg <sup>4</sup>
Acute toxicity (dermal)	ATEmix = 1820.91 mg/kg (Category 4) Butanoxime LD50 (rabbit) dermal = 1000.00 mg/kg <sup>1</sup> PETROLEUM ETHER LD50 (rabbit) dermal = 2000.00 mg/kg <sup>3</sup>
Acute toxicity (inhalation)	Not available
Skin corrosion and skin irritation	Causes skin irritation (Xylene)
Serious eye damage or eye irritation	Causes serious eye irritation (Butanoxime)
Respirator and skin sensitization	Not classified
Skin sentization	May cause an allergic skin reaction (Butanoxime)
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity following single exposure	Not classified
Specific target organ toxicity following repeated exposure	Causes damage to organs through prolonged or repeated exposure (Ethyl Benzene,PETROLEUM ETHER)
Aspiration hazard	May be fatal if swallowed and enters airways (Ethyl Benzene,PETROLEUM ETHER)

## 12. ECOLOGICAL INFORMATION

Acute aquatic hazard	Toxic to aquatic life <u>Butanoxime</u> LC50 (fish) 96 hr = 100 mg/L <sup>1</sup> EC48 (shrimp) 48 hr = 201 mg/L <sup>1</sup> ErC-EC72 (Fungi) 96 hr = 6.09 mg/L <sup>1</sup> <u>Ethyl Benzene</u> LC50 (fish) 96 hr = 4.20 mg/L <sup>9</sup> EC48 (shrimp) 48 hr = 2.10 mg/L <sup>8</sup> ErC-EC72 (Fungi) 96 hr = 4.60 mg/L <sup>8</sup> <u>Xylene</u> LC50 (fish) 96 hr = 3.30 mg/L <sup>5</sup> <u>lead(2+) ion dioxochromiumbis(olate)</u> EC48 (shrimp) 48 hr = 100 mg/L <sup>4</sup> ErC-EC72 (Fungi) 96 hr = 100 mg/L <sup>4</sup>
Long term aquatic hazard	Very toxic to aquatic life with long lasting effects <u>Butanoxime</u> NOEC fish = 50 mg/L <sup>1</sup> NOEC shrimp = 100 mg/L <sup>1</sup> NOEC fungi = 2.56 mg/L <sup>1</sup> <u>Ethyl Benzene</u> NOEC fish = 3.30 mg/L <sup>8</sup> NOEC shrimp = 1 mg/L <sup>8</sup> NOEC fungi = 3.4 mg/L <sup>8</sup> <u>Xylene</u> NOEC fish = 1.30 mg/L <sup>10</sup> NOEC shrimp = 1.57 mg/L <sup>6</sup> NOEC fungi = 0.44 mg/L <sup>6</sup> <u>lead(2+) ion dioxochromiumbis(olate)</u>



	<del>lead(+) ion dihydrogenphosphate</del>
	NOEC fish = 1 mg/L <sup>4</sup>
	NOEC shrimp = 0.07 mg/L <sup>4</sup>
Persistence and degradability	Rapidly degradable (Butanoxime,Ethyl Benzene,Xylene)
Bioaccumulative potential	Bioaccumulative potential
	<u>Butanoxime</u>
	log KOW = 0.63 <sup>12</sup>
	BCF = 0.5 <sup>12</sup>
	<u>Ethyl Benzene</u>
	log KOW = 3.03 <sup>8</sup>
	BCF = 110 <sup>8</sup>
	<u>Xylene</u>
	log KOW = 3.20 <sup>13</sup>
	BCF = 14.80 <sup>13</sup>
Mobility in soil	The product is insoluable in water. If released to water, some of the components will have tendency to evaporate while other components are expected to be highly mobile in soil and have the potential to reach underground water supplies.
Other adverse effects	Not available

### 13. DISPOSAL CONSIDERATIONS

Disposal methods	Disposing of this material/container should be done under all the regulations or handled by authorized waste collector in your country
Container disposal	Do not re-use empty containers

### 14. TRANSPORT INFORMATION

Labels required



UN number	1263
UN proper shipping name	Paint
Transport hazard class(es)	3
Packing group	III
Environmental hazards	Not applicable
Special precautions	Not applicable
Transport in bulk	Not applicable

### 15. REGULATORY INFORMATION

Inventory of existing chemical substance produced or imported in USA (TSCA)	All component in this product are listed
Toxic substance control act (TSCA)	All component in this product are listed

### 16. OTHER INFORMATION

Issue date: 24 June 2025

References

1. <https://echa.europa.eu/brief-profile/-/briefprofile/100.002.270> (23-10-19)
2. <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~0KYTYa:3> (03-05-19)
3. <https://echa.europa.eu/brief-profile/-/briefprofile/100.059.242> (24-12-19)
4. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.267> (17-12-19)
5. <https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/682> (04-05-19)
6. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124> (24-12-19)
7. <https://echa.europa.eu/brief-profile/-/briefprofile/100.059.242> (14/8/19)
8. <https://echa.europa.eu/brief-profile/-/briefprofile/100.002.591> (03-05-19)
9. <https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/1574> (03-05-19)

https://www.epa.gov/chemical-safety/chemical-safety-data-sheet-csdh-chemical-safety-data-sheet-csdh

10. <https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124> (04-05-19)

11. -

12. <https://pubchem.ncbi.nlm.nih.gov/compound/7292#section=Environmental-Abiotic-Degradation> (23-10-19)

13. <https://pubchem.ncbi.nlm.nih.gov/compound/7929#section=Environmental-Fate> (04-05-19)

14. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=13> (25-12-19)

15. <https://www.osha.gov/chemicaldata/chemResult.html?recNo=228> (04-05-19)

16. Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (20-8-2024)

17. Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (20-8-24)

18. Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (21-8-2024)