

1. IDENTIFICATION OF THE MIXTURE AND OF THE SUPPLIER

Product Identifier

Product	Epoxy Primer Green [58-3016L]
Recommended use of chemical	Use as primer
Restriction on use	No open flames, No sparks, and No smoking

Supplier's details

Company	Big-Ben (Paints) Company Limited
Address	38 Mu 7 Suanluangruamjai Road Suanluang Krathumban Samutsakorn 74110 Thailand
Telephone number	+66 2 811 1442 or +66 2 811 1443
Fax number	+66 2 811 0632
E-mail	bbp@bbp.co.th
Emergency phone number	+66 2 811 1442 or + 66 2 811 1443

2. HAZARD IDENTIFICATION

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CSR 1910.1200; the SDS and labels contain all the information as required by the standard.

Flammable liquids	Category 2
Acute toxicity - oral	Category 3
Skin corrosion/irritation	Category 2
Eye damage/irritation	Category 1
Sensitization - skin	Category 1
Specific target organ toxicity (single exposure)	Category 3
Hazardous to the aquatic environment - acute hazard	Category 1
Hazardous to the aquatic environment - long-term hazard	Category 1

Remark:

Percentage of mixture consisting of ingredient(s) of unknown oral toxicity: 61.63%

Percentage of mixture consisting of ingredient(s) of unknown dermal toxicity: 99.14%

Percentage of mixture consisting of ingredient(s) of unknown inhalation toxicity: 68.12%

GHS label elements

Pictogram or symbol



Signal word

Danger

Hazard statement:

- H225 Highly Flammable liquid and vapour
- H301 Toxic if swallowed
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects

Precautionary statement

[PREVENTION]

- P210 Keep away from heat / sparks / open flames / hot surfaces. No smoking.
- P233 Keep container tightly closed.

P240 Ground / bond container and receiving equipment.
P241 Use explosion-proof electrical / ventilating / lighting / equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves / protective clothing / eye protection / face protection.

[RESPONSE]

P301+P310 IF SWALLOWED Immediately call a POISON CENTER or doctor / physician.
P302+P352 IF ON SKIN Wash with plenty of soap and water.
P303+P361+P353 IF ON SKIN (or hair) Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
P304+P340 IF INHALED Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor / physician.
P312 Call a POISON CENTER or doctor / physician if you feel unwell.
P321 Specific treatment (see on this label).
P330 Rinse mouth.
P332+P313 IF skin irritation occurs Get medical advice / attention.
P333+P313 IF skin irritation or rash occurs Get medical advice / attention.
P362 Take off contaminated clothing and wash before reuse.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P391 Collect spillage.

[STORAGE]

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

[DISPOSAL]

P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Content % (w/w)
2-Methylpropanol-1;2-Methylpropyl alcohol	78-83-1	2.18 - 4.11
Barite	7727-43-7	5.10 - 12.77
Epoxy Resin	25068-38-6	12.88 - 32.80
Fumed Silica	112945-52-5	0.83 - 1.26
Magnesium Dioxide	1309-48-4	2.31 - 7.11
Silicon Dioxide	7631-86-9	9.42 - 15.81
Titanium Dioxide	13463-67-7	6.51 - 10.90
Xylene	1330-20-7	11.48 - 34.07
dizinc(2+) potassium bis(dioxochromiumbis(olate)) hydroxide	11103-86-9	4.53 - 8.47

4. FIRST AID MEASURES

Inhalation	Remove to fresh air. If unconscious, place in recovery position and seek medical attention immediately.
Skin contact	Immediately flush with water for at least 15 minutes. Remove contaminated clothing. Seek medical attention immediately. Wash thoroughly after handling.



SAFETY DATA SHEET

Eye contact	Hold eyelids apart and immediately flush with plenty of water for 15 minutes. Seek medical advice. Remove contact lenses.
Ingestion	Rinse mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.
Most important symptoms/effects, acute and delayed	Dizziness. Drowsiness. Headache. Nausea. Vomiting. Weakness. Unconsciousness. Skin and eye redness. Pain. Nausea. Vomiting.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media	Dry chemical. Carbon Dioxide (CO ₂). Alcohol-resistant foam. Water spray.
Unsuitable extinguishing media	High volume water jet.
Specific hazards arising from the chemical	Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Container may rupture on heating.
Specific protective equipment and precautions for firefighters	Wear self-contained breathing apparatus and full protective clothing for firefighting.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures	Keep unnecessary personnel away. Prevent further leakage or spillage if safe to do so. Use personal protective equipment. Use only non-sparking tools.
Environmental precautions	Prevent the material from entering drains or water courses.
Methods and materials for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations.

7. HANDLING AND STORAGE

Precautions for safe handling	Avoid breathing vapor and contact with eyes, skin, and clothing. Do not leave containers open. Avoid repeated or prolonged contact with skin.
Conditions for safe storage, including any incompatibilities	Keep away from heat or flames. Keep in cool, dry, ventilated storage and in closed containers. Store away from oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters	<u>2-Methylpropanol-1;2-Methylpropyl alcohol</u> OSHA PEL-TWA 100 ¹⁵ Skin notification N ¹⁵ NIOSH REL-TWA 50 ¹⁵ Skin notification N ¹⁵ ACGIH Skin notification N ¹⁵ CAL/OSHA Skin notification N ¹⁵ Safe Work Australia (Australia, 4/2024) TWA : 50 ppm 8 hours. ¹⁹ TWA : 152 mg/m ³ 8 hours. ¹⁹ <u>Barite</u> OSHA Skin notification N ¹⁸ NIOSH Skin notification N ¹⁸ ACGIH Skin notification N ¹⁸ CAL/OSHA Skin notification N ¹⁸ Safe Work Australia (Australia, 4/2024) TWA : 4 (inhalable), 1.35 (respirable) mg/m ³ 8 hours. ¹⁹ Safe Work Australia (Australia, 4/2024) TWA : 10 mg/m ³ 8 hours. ¹⁹
--------------------	--

Safe Work Australia (Australia, 4/2024)

TWA : 2 mg/m³ 8 hours. ²¹

Titanium Dioxide

OSHA

PEL-TWA 15¹⁶

Skin notification N¹⁶

NIOSH

Skin notification N¹⁶

ACGIH

TLV-TWA 10¹⁶

Skin notification N¹⁶

CAL/OSHA

PEL-TWA 10¹⁶

Skin notification N¹⁶

Safe Work Australia (Australia, 4/2024)

TWA : 10 mg/m³ 8 hours. ²⁰

Xylene

OSHA

PEL-TWA 100¹⁷

Skin notification N¹⁷

NIOSH

REL-TWA 100¹⁷

Skin notification N¹⁷

ACGIH

TLV-TWA 100¹⁷

TLV-STEL 150¹⁷

Skin notification N¹⁷

CAL/OSHA

PEL-TWA 100¹⁷

PEL-STEL 150¹⁷

PEL-C 300¹⁷

Skin notification N¹⁷

Safe Work Australia (Australia, 4/2024)

TWA : 80 ppm 8 hours. ²⁰

TWA : 350 mg/m³ 8 hours. ²⁰

STEL : 150 ppm 15 minutes. ²⁰

STEL : 655 mg/m³ 15 minutes. ²⁰

Appropriate engineering controls

Provide adequate ventilation. Install local exhaust.

Personal protective equipment

Respiratory protection

Organic vapor respirator

Hand protection

Rubber gloves. Neoprene.

Eye protection

Safety goggle.

Skin and body protection

Wear suitable clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state

High Viscosity liquid

Colour

Green

Odour

Organic solvent

pH

Not available

Melting point/freezing point

Not Available

Boiling point or initial boiling point
and boiling range

139.5 °C (283.1 °F) (Xylene)

Flash point

18.0 °C (64.4 °F) (Xylene)

Flammability

Flammable

Lower and upper explosion limit/flammability limit	Not Available
Vapour pressure	16 hPa at 20 °C (2-Methylpropanol-1;2-Methylpropyl alcohol)
Density and/or relative density	1.38 - 1.48 g/cm ³
Relative vapour density	Not Available
Solubility	Soluble in Organic solvent
Partition coefficient n-octanol/water (log value)	Not applicable
Auto-ignition temperature	187.5 °C (369.5 °F) (Xylene)
Decomposition temperature	Not applicable
Viscosity	90 - 100 KU at 30 °C
Particle characteristics	Not applicable

10. STABILITY AND REACTIVITY

Reactivity	Reacts violently with strong acids and strong oxidants
Chemical stability	Stable under normal storage and handling conditions
Possibility of hazardous reaction	Will not occur
Condition to avoid	High temperatures, sparks, open flame, and all other sources of ignition
Incompatible materials	Strong oxidizing agents, strong acids
Hazardous decomposition products	Not available

11. TOXICOLOGICAL INFORMATION

Acute toxicity (oral)	ATEmix = 288.89 mg/kg (Category 3) 2-Methylpropanol-1;2-Methylpropyl alcoho LD50 (rat) oral = 2460.00 mg/kg ¹ Barite LD50 (rat) oral = 30700.00 mg/kg ² Fumed Silica LD50 (rat) oral = 22500.00 mg/kg ³ Magnesium Dioxide LD50 (rat) oral = 3870.00 mg/kg Titanium Dioxide LD50 (rat) oral = 10000.00 mg/kg ⁴ dizinc(2+) potassium bis(dioxochromiumbis(olate)) hydroxide LD50 (rat) oral = 57.18 mg/kg ⁵
Acute toxicity (dermal)	Not available
Acute toxicity (inhalation)	ATEmix = 1740.07 mg/kg (Not classified) Xylene LC50 (rat) inhalation = 6360.00 mg/kg ⁶ dizinc(2+) potassium bis(dioxochromiumbis(olate)) hydroxide LC50 (rat) inhalation = 510.00 mg/kg ⁵
Skin corrosion and skin irritation	Causes skin irritation (2-Methylpropanol-1;2-Methylpropyl alcoho,Epoxy Resin,Xylene)
Serious eye damage or eye irritation	Causes serious eye damage (2-Methylpropanol-1;2-Methylpropyl alcoho,Epoxy Resin)
Respirator and skin sensitization	Not classified
Skin sensitization	May cause an allergic skin reaction (Epoxy Resin)
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity following single exposure	May cause respiratory irritation (2-Methylpropanol-1;2-Methylpropyl alcoho)
Specific target organ toxicity following repeated exposure	Not classified
Aspiration hazard	Not classified

12. ECOLOGICAL INFORMATION

Acute aquatic hazard	Very toxic to aquatic life <u>2-Methylpropanol-1;2-Methylpropyl alcoho</u> LC50 (fish) 96 hr = 1430 mg/L ⁷ EC48 (shrimp) 48 hr = 1100 mg/L ⁷ ErC-EC72 (Fungi) 96 hr = 593 mg/L ⁷ <u>Barite</u> LC50 (fish) 96 hr = 3.5 mg/L ¹⁰
----------------------	--

EC48 (shrimp) 48 hr = 14.5 mg/L¹⁰
 ErC-EC72 (Fungi) 96 hr = 1.15 mg/L¹⁰
Epoxy Resin
 EC48 (shrimp) 48 hr = 2 mg/L⁸
Titanium Dioxide
 EC48 (shrimp) 48 hr = 100 mg/L⁴
 ErC-EC72 (Fungi) 96 hr = 35.9 mg/L⁴
Xylene
 LC50 (fish) 96 hr = 3.30 mg/L⁶
dizinc(2+) potassium bis(dioxochromiumbis(olate)) hydroxide
 LC50 (fish) 96 hr = 0.33 mg/L⁵
 EC48 (shrimp) 48 hr = 0.155 mg/L⁵
 ErC-EC72 (Fungi) 96 hr = 0.1125 mg/L⁵

Long term aquatic hazard

Very toxic to aquatic life with long lasting effects

2-Methylpropanol-1;2-Methylpropyl alcoho
 NOEC shrimp = 20 mg/L⁷
 NOEC fungi = 53 mg/L⁷

Barite
 NOEC fish = 1.26 mg/L¹⁰
 NOEC shrimp = 2.9 mg/L¹⁰
 NOEC fungi = 1.15 mg/L¹⁰

Titanium Dioxide
 NOEC shrimp = 1.72 mg/L¹²
 NOEC fungi = 1 mg/L¹²

Xylene
 NOEC fish = 1.30 mg/L¹¹
 NOEC shrimp = 1.57 mg/L⁹
 NOEC fungi = 0.44 mg/L⁹

dizinc(2+) potassium bis(dioxochromiumbis(olate)) hydroxide
 NOEC fish = 0.056 mg/L⁵
 NOEC shrimp = 0.075 mg/L⁵
 NOEC fungi = 0.01 mg/L⁵

Persistence and degradability

Rapidly degradable (2-Methylpropanol-1;2-Methylpropyl alcoho,Xylene)

Bioaccumulative potential

Bioaccumulative potential

2-Methylpropanol-1;2-Methylpropyl alcoho
 log KOW = 0.76¹³
 BCF = 3¹³

Xylene
 log KOW = 3.20¹⁴
 BCF = 14.80¹⁴

Mobility in soil

The product is insoluable in water. If released to water, some of the components will have tendency to evaporate while other components are expected to be highly mobile in soil and have the potential to reach underground water supplies.

Other adverse effects

Not available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Disposing of this material/container should be done under all the regulations or handled by authorized waste collector in your country

Container disposal

Do not re-use empty containers

14. TRANSPORT INFORMATION

Labels required



UN number

1263

UN proper shipping name

Paint

Transport hazard class(es)

3

Packing group

III

Environmental hazards	Not applicable
Special precautions	Not applicable
Transport in bulk	Not applicable

15. REGULATORY INFORMATION

Inventory of existing chemical substance produced or imported in USA (TSCA)	All component in this product are listed
Toxic substance control act (TSCA)	All component in this product are listed

16. OTHER INFORMATION

Issue date: 14 March 2025

References

1. [https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~9YNeeY:1\(11-7-19\)](https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~9YNeeY:1(11-7-19))
2. [https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~8BKX2:3\(21/8/19\)](https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~8BKX2:3(21/8/19))
3. [https://pubchem.ncbi.nlm.nih.gov/compound/24261#section=Non-Human-Toxicity-Excerpts\(24-12-19\)](https://pubchem.ncbi.nlm.nih.gov/compound/24261#section=Non-Human-Toxicity-Excerpts(24-12-19))
4. [https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~Q1zAvm:3\(3-5-19\)](https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~Q1zAvm:3(3-5-19))
5. [https://echa.europa.eu/brief-profile/-/briefprofile/100.031.196\(16-12-19\)](https://echa.europa.eu/brief-profile/-/briefprofile/100.031.196(16-12-19))
6. [https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/682\(04-05-19\)](https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/682(04-05-19))
7. [https://echa.europa.eu/brief-profile/-/briefprofile/100.001.044\(11-7-19\)](https://echa.europa.eu/brief-profile/-/briefprofile/100.001.044(11-7-19))
8. [https://echa.europa.eu/brief-profile/-/briefprofile/100.105.541\(17-12-19\)](https://echa.europa.eu/brief-profile/-/briefprofile/100.105.541(17-12-19))
9. [https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124\(24-12-19\)](https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124(24-12-19))
10. [https://echa.europa.eu/brief-profile/-/briefprofile/100.028.896\(21/8/19\)](https://echa.europa.eu/brief-profile/-/briefprofile/100.028.896(21/8/19))
11. [https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124\(04-05-19\)](https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124(04-05-19))
12. [https://echa.europa.eu/brief-profile/-/briefprofile/100.033.327\(3-5-19\)](https://echa.europa.eu/brief-profile/-/briefprofile/100.033.327(3-5-19))
13. [https://pubchem.ncbi.nlm.nih.gov/compound/6560#section=Octanol-Water-Partition-Coefficient\(11-7-19\)](https://pubchem.ncbi.nlm.nih.gov/compound/6560#section=Octanol-Water-Partition-Coefficient(11-7-19))
14. [https://pubchem.ncbi.nlm.nih.gov/compound/7929#section=Environmental-Fate\(04-05-19\)](https://pubchem.ncbi.nlm.nih.gov/compound/7929#section=Environmental-Fate(04-05-19))
15. [https://www.osha.gov/chemicaldata/chemResult.html?recNo=676\(11-7-19\)](https://www.osha.gov/chemicaldata/chemResult.html?recNo=676(11-7-19))
16. [https://www.osha.gov/chemicaldata/chemResult.html?recNo=246\(3-5-19\)](https://www.osha.gov/chemicaldata/chemResult.html?recNo=246(3-5-19))
17. [https://www.osha.gov/chemicaldata/chemResult.html?recNo=228\(04-05-19\)](https://www.osha.gov/chemicaldata/chemResult.html?recNo=228(04-05-19))
18. [https://www.osha.gov/chemicaldata/chemResult.html?recNo=635\(21/8/19\)](https://www.osha.gov/chemicaldata/chemResult.html?recNo=635(21/8/19))
19. Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (20-8-2024)
20. Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (21-8-2024)
21. Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (20-8-24)