

1. IDENTIFICATION OF THE MIXTURE AND OF THE SUPPLIER

Product Identifier

Product	Light Polyester Putty RGB [83-6600]
Recommended use of chemical	Use as putty
Restriction on use	No open flames, No sparks, and No smoking

Supplier's details

Company	Big-Ben Chemical Company Limited
Address	168 Mu 2 Donkhaidee Krathumban Samutsakorn 74110 Thailand
Telephone number	+66 2 811 1442 or +66 2 811 1443
Fax number	+66 2 811 0632
E-mail	bbp@bbp.co.th
Emergency phone number	+66 2 811 1442 or + 66 2 811 1443

2. HAZARD IDENTIFICATION

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CSR 1910.1200; the SDS and labels contain all the information as required by the standard.

Flammable liquids	Category 3
Acute toxicity - oral	Category 5
Skin corrosion/irritation	Category 2
Eye damage/irritation	Category 2A
Toxic to reproduction	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Hazardous to the aquatic environment - acute hazard	Category 1

Remark:

Percentage of mixture consisting of ingredient(s) of unknown oral toxicity: 64.43%

Percentage of mixture consisting of ingredient(s) of unknown dermal toxicity: 99.02%

Percentage of mixture consisting of ingredient(s) of unknown inhalation toxicity: 99.02%

GHS label elements

Pictogram or symbol



Signal word

Danger

Hazard statement:

H226 Flammable liquid and vapour

H303 May be harmful if swallowed

H315 Causes skin irritation

H319 Causes serious eye irritation

H361 Suspected of damaging fertility or the unborn child

H372 Causes damage to organs through prolonged or repeated exposure

H400 Very toxic to aquatic life

Precautionary statement

[PREVENTION]

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground / bond container and receiving equipment.

- P241 Use explosion-proof electrical / ventilating / lighting / equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust / fume / gas / mist / vapors / spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / protective clothing / eye protection / face protection.

[RESPONSE]

- P302+P352 IF ON SKIN Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair) Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
- P305+P351+P338 IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned Get medical advice / attention.
- P312 Call a POISON CENTER or doctor / physician if you feel unwell.
- P314 Get medical advice / attention if you feel unwell.
- P321 Specific treatment (see on this label).
- P332+P313 IF skin irritation occurs Get medical advice / attention.
- P337+P313 IF eye irritation persists Get medical advice / attention.
- P362 Take off contaminated clothing and wash before reuse.
- P370+P378 In case of fire Use dry sand, dry chemical or alcohol-resistant foam for extinction.
- P391 Collect spillage.

[STORAGE]

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

[DISPOSAL]

- P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Content % (w/w)
Magnesium Dioxide	1309-48-4	15.74 - 18.23
Silicon dioxide	14808-60-7	23.61 - 27.34
Talcum powder	14807-96-6	16.20 - 18.76
Titanium Dioxide	13463-67-7	3.47 - 4.02
Unsaturated polyester resin	64386-67-0	22.00 - 25.47
styrene	100-42-5	13.97 - 16.17

4. FIRST AID MEASURES

Inhalation	Remove to fresh air. If unconscious, place in recovery position and seek medical attention immediately.
Skin contact	Immediately flush with water for at least 15 minutes. Remove contaminated clothing. Seek medical attention immediately. Wash thoroughly after handling.
Eye contact	Hold eyelids apart and immediately flush with plenty of water for 15 minutes. Seek medical advice. Remove contact lenses.
Ingestion	Rinse mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.
Most important symptoms/effects, acute and delayed	Dizziness. Drowsiness. Headache. Nausea. Vomiting. Weakness. Unconsciousness. Skin and eye redness. Pain. Nausea. Vomiting.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media	Dry chemical. Carbon Dioxide (CO ₂). Alcohol-resistant foam. Water spray.
Unsuitable extinguishing media	High volume water jet.
Specific hazards arising from the chemical	Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Container may rupture on heating.

Specific protective equipment and precautions for firefighters

Wear self-contained breathing apparatus and full protective clothing for firefighting.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Keep unnecessary personnel away. Prevent further leakage or spillage if safe to do so. Use personal protective equipment. Use only non-sparking tools.

Environmental precautions

Prevent the material from entering drains or water courses.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid breathing vapor and contact with eyes, skin, and clothing. Do not leave containers open. Avoid repeated or prolonged contact with skin.

Conditions for safe storage, including any incompatibilities

Keep away from heat or flames. Keep in cool, dry, ventilated storage and in closed containers. Store away from oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Safe Work Australia (Australia, 4/2024)

TWA : 10 mg/m³ 8 hours. ⁹

Silicon dioxide

OSHA

Skin notification N¹³

NIOSH

Skin notification N¹³

ACGIH

Skin notification N¹³

CAL/OSHA

Skin notification N¹³

Safe Work Australia (Australia, 4/2024)

TWA : 0.05 mg/m³ 8 hours. ⁸

Talcum powder

OSHA

PEL-TWA 20 mppcf⁶

Skin notification N

NIOSH

REL-TWA 2 mg/m³ (resp)

Skin notification N

ACGIH

TLV-TWA 2 mg/m³ (respirable particulate matter) [2009]

Skin notification N

CAL/OSHA

PEL-TWA 2 mg/m³ (respirable dust)

Skin notification N

Safe Work Australia (Australia, 4/2024)

TWA : 2 mg/m³ 8 hours. ⁸

Titanium Dioxide

OSHA

PEL-TWA 15¹²

Skin notification N¹²

NIOSH

Skin notification N¹²

ACGIH

TLV-TWA 10¹²

Skin notification N¹²

CAL/OSHA

PEL-TWA 10¹²
 Skin notification N¹²
 Safe Work Australia (Australia, 4/2024)
 TWA : 10 mg/m³ 8 hours. ⁸
styrene
 OSHA
 PEL-TWA 100 ppm⁷
 PEL-C 200 ppm; 600 ppm (Peak) for a single time period up to 5 min in any 3 hours
 Skin notification N
 NIOSH
 REL-TWA 50 ppm (215 mg/m³)
 REL-STEEL 100 ppm (425 mg/m³)
 Skin notification N
 ACGIH
 TLV-TWA 20 ppm [1996]
 TLV-STEEL 40 ppm [1996]
 Skin notification N
 CAL/OSHA
 PEL-TWA 50 ppm (215 mg/m³)
 PEL-STEEL 100 ppm (425 mg/m³)
 PEL-C 500 ppm
 Skin notification Y
 Safe Work Australia (Australia, 4/2024)
 TWA : 20 ppm 8 hours. ⁸
 TWA : 85 mg/m³ 8 hours. ⁸
 STEL : 40 ppm 15 minutes. ⁸
 STEL : 170 mg/m³ 15 minutes. ⁸
 Provide adequate ventilation. Install local exhaust.

Appropriate engineering controls

Personal protective equipment

Respiratory protection	Organic vapor respirator
Hand protection	Rubber gloves. Neoprene.
Eye protection	Safety goggle.
Skin and body protection	Wear suitable clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Paste
Colour	Yellow
Odour	Organic solvent
pH	Not available
Melting point/freezing point	Not available
Boiling point or initial boiling point and boiling range	143.0 °C (289.4 °F) (styrene)
Flash point	31.0 °C (87.8 °F) (styrene)
Flammability	Flammable
Lower and upper explosion limit/flammability limit	
Vapour pressure	6 hPa at 20 °C (styrene)
Density and/or relative density	1.6 - 1.75 g/cm ³
Relative vapour density	
Solubility	Soluble in Organic solvent
Partition coefficient n-octanol/water (log value)	Not applicable

Auto-ignition temperature	490.0 °C (914.0 °F) (styrene)
Decomposition temperature	Not applicable
Viscosity	135 - 140 KU at 30 °C
Particle characteristics	Not applicable

10. STABILITY AND REACTIVITY

Reactivity	Reacts violently with strong acids and strong oxidants
Chemical stability	Stable under normal storage and handling conditions
Possibility of hazardous reaction	Will not occur
Condition to avoid	High temperatures, sparks, open flame, and all other sources of ignition
Incompatible materials	Strong oxidizing agents, strong acids
Hazardous decomposition products	Not available

11. TOXICOLOGICAL INFORMATION

Acute toxicity (oral)	ATEmix = 4603.22 mg/kg (Category 5) Magnesium Dioxide LD50 (rat) oral = 3870.00 mg/kg Titanium Dioxide LD50 (rat) oral = 10000.00 mg/kg ¹⁰ styrene LD50 (rat) oral = 5000.00 mg/kg ²
Acute toxicity (dermal)	Not available
Acute toxicity (inhalation)	Not available
Skin corrosion and skin irritation	Causes skin irritation (styrene)
Serious eye damage or eye irritation	Causes serious eye irritation (styrene)
Respirator and skin sensitization	Not classified
Skin sentization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Suspected of damaging fertility or the unborn child (styrene)
Specific target organ toxicity following single exposure	Not classified
Specific target organ toxicity following repeated exposure	Causes damage to organs through prolonged or repeated exposure (styrene)
Aspiration hazard	Not classified

12. ECOLOGICAL INFORMATION

Acute aquatic hazard	Very toxic to aquatic life <u>Talcum powder</u> LC50 (fish) 96 hr = 0.089 mg/L ³ EC48 (shrimp) 48 hr = 0.00368 mg/L ErC-EC72 (Fungi) 96 hr = 0.007203 mg/L <u>Titanium Dioxide</u> EC48 (shrimp) 48 hr = 100 mg/L ¹⁰ ErC-EC72 (Fungi) 96 hr = 35.9 mg/L ¹⁰ <u>styrene</u> LC50 (fish) 96 hr = 9.1 mg/L EC48 (shrimp) 48 hr = 4.7 mg/L ErC-EC72 (Fungi) 96 hr = 0.72 mg/L
Long term aquatic hazard	No information
Persistence and degradability	Rapidly degradable (styrene)
Bioaccumulative potential	Bioaccumulative potential <u>styrene</u> log KOW = 2.95 BCF = 12-140
Mobility in soil	The product is insoluable in water. If released to water, some of the components will have tendency to

Other adverse effects	evaporate while other components are expected to be highly mobile in soil and have the potential to reach underground water supplies. Not available
-----------------------	--

13. DISPOSAL CONSIDERATIONS

Disposal methods	Disposing of this material/container should be done under all the regulations or handled by authorized waste collector in your country
Container disposal	Do not re-use empty containers

14. TRANSPORT INFORMATION

Labels required



UN number	1263
UN proper shipping name	Paint
Transport hazard class(es)	3
Packing group	III
Environmental hazards	Not applicable
Special precautions	Not applicable
Transport in bulk	Not applicable

15. REGULATORY INFORMATION

Inventory of existing chemical substance produced or imported in USA (TSCA)	All component in this product are listed
Toxic substance control act (TSCA)	All component in this product are listed

16. OTHER INFORMATION

Issue date: 18 June 2025

References

- <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~tL93nR:1> (3-5-19)
- <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~lu5BAV:1> (03-05-19)
- <https://echa.europa.eu/brief-profile/-/briefprofile/100.035.328> (7/8/19)
- <https://echa.europa.eu/brief-profile/-/briefprofile/100.006.765> (3-5-19)
- <https://www.osha.gov/chemicaldata/chemResult.html?recNo=220> (3-5-19)
- <https://www.osha.gov/chemicaldata/chemResult.html?recNo=277> (7/8/19)
- <https://www.osha.gov/chemicaldata/chemResult.html?recNo=14> (7/8/19)
- Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (21-8-2024)
- Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (20-8-2024)
- <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~Q1zAvm:3> (3-5-19)
- <https://echa.europa.eu/brief-profile/-/briefprofile/100.033.327> (3-5-19)
- <https://www.osha.gov/chemicaldata/chemResult.html?recNo=246> (3-5-19)
- <https://www.osha.gov/chemicaldata/chemResult.html?recNo=278> (17-12-19)