

1. IDENTIFICATION OF THE MIXTURE AND OF THE SUPPLIER

Product Identifier

| | |
|-----------------------------|---|
| Product | Light Polyester Putty RGB [83-6600] |
| Recommended use of chemical | Use as putty |
| Restriction on use | No open flames, No sparks, and No smoking |

Supplier's details

| | |
|------------------------|---|
| Company | Big-Ben Chemical Company Limited |
| Address | 168 Mu 2 Donkhaidee Krathumban Samutsakorn 74110 Thailand |
| Telephone number | +66 2 811 1442 or +66 2 811 1443 |
| Fax number | +66 2 811 0632 |
| E-mail | bbp@bbp.co.th |
| Emergency phone number | +66 2 811 1442 or + 66 2 811 1443 |

2. HAZARD IDENTIFICATION

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CSR 1910.1200; the SDS and labels contain all the information as required by the standard.

| | |
|---|-------------|
| Flammable liquids | Category 3 |
| Acute toxicity - oral | Category 5 |
| Skin corrosion/irritation | Category 2 |
| Eye damage/irritation | Category 2A |
| Toxic to reproduction | Category 2 |
| Specific target organ toxicity (repeated exposure) | Category 1 |
| Hazardous to the aquatic environment - acute hazard | Category 1 |

Remark:

Percentage of mixture consisting of ingredient(s) of unknown oral toxicity: 64.43%

Percentage of mixture consisting of ingredient(s) of unknown dermal toxicity: 99.02%

Percentage of mixture consisting of ingredient(s) of unknown inhalation toxicity: 99.02%

GHS label elements

Pictogram or symbol



Signal word

Danger

Hazard statement:

- H226 Flammable liquid and vapour
- H303 May be harmful if swallowed
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H361 Suspected of damaging fertility or the unborn child
- H372 Causes damage to organs through prolonged or repeated exposure
- H400 Very toxic to aquatic life

Precautionary statement

[PREVENTION]

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat / sparks / open flames / hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground / bond container and receiving equipment.

- P241 Use explosion-proof electrical / ventilating / lighting / equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust / fume / gas / mist / vapors / spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P280 Wear protective gloves / protective clothing / eye protection / face protection.

[RESPONSE]

- P302+P352 IF ON SKIN Wash with plenty of soap and water.
P303+P361+P353 IF ON SKIN (or hair) Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
P305+P351+P338 IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned Get medical advice / attention.
P312 Call a POISON CENTER or doctor / physician if you feel unwell.
P314 Get medical advice / attention if you feel unwell.
P321 Specific treatment (see on this label).
P332+P313 IF skin irritation occurs Get medical advice / attention.
P337+P313 IF eye irritation persists Get medical advice / attention.
P362 Take off contaminated clothing and wash before reuse.
P370+P378 In case of fire Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P391 Collect spillage.

[STORAGE]

- P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

[DISPOSAL]

- P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

| Chemical name | CAS No. | Content % (w/w) |
|-----------------------------|------------|-----------------|
| Magnesium Dioxide | 1309-48-4 | 15.74 - 18.23 |
| Silicon dioxide | 14808-60-7 | 23.61 - 27.34 |
| Talcum powder | 14807-96-6 | 16.20 - 18.76 |
| Titanium Dioxide | 13463-67-7 | 3.47 - 4.02 |
| Unsaturated polyester resin | 64386-67-0 | 22.00 - 25.47 |
| styrene | 100-42-5 | 13.97 - 16.17 |

4. FIRST AID MEASURES

| | |
|--|--|
| Inhalation | Remove to fresh air. If unconscious, place in recovery position and seek medical attention immediately. |
| Skin contact | Immediately flush with water for at least 15 minutes. Remove contaminated clothing. Seek medical attention immediately. Wash thoroughly after handling. |
| Eye contact | Hold eyelids apart and immediately flush with plenty of water for 15 minutes. Seek medical advice. Remove contact lenses. |
| Ingestion | Rinse mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. |
| Most important symptoms/effects, acute and delayed | Dizziness. Drowsiness. Headache. Nausea. Vomiting. Weakness. Unconsciousness. Skin and eye redness. Pain. Nausea. Vomiting. |

5. FIRE FIGHTING MEASURES

| | |
|--|--|
| Suitable extinguishing media | Dry chemical. Carbon Dioxide (CO ₂). Alcohol-resistant foam. Water spray. |
| Unsuitable extinguishing media | High volume water jet. |
| Specific hazards arising from the chemical | Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Container may rupture on heating. |

Specific protective equipment and precautions for firefighters

Wear self-contained breathing apparatus and full protective clothing for firefighting.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Keep unnecessary personnel away. Prevent further leakage or spillage if safe to do so. Use personal protective equipment. Use only non-sparking tools.

Environmental precautions

Prevent the material from entering drains or water courses.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid breathing vapor and contact with eyes, skin, and clothing. Do not leave containers open. Avoid repeated or prolonged contact with skin.

Conditions for safe storage, including any incompatibilities

Keep away from heat or flames. Keep in cool, dry, ventilated storage and in closed containers. Store away from oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Safe Work Australia (Australia, 4/2024)

TWA : 10 mg/m³ 8 hours. ⁹

Silicon dioxide

OSHA

Skin notification N¹³

NIOSH

Skin notification N¹³

ACGIH

Skin notification N¹³

CAL/OSHA

Skin notification N¹³

Safe Work Australia (Australia, 4/2024)

TWA : 0.05 mg/m³ 8 hours. ⁸

Talcum powder

OSHA

PEL-TWA 20 mppcf⁶

Skin notification N

NIOSH

REL-TWA 2 mg/m³ (resp)

Skin notification N

ACGIH

TLV-TWA 2 mg/m³ (respirable particulate matter) [2009]

Skin notification N

CAL/OSHA

PEL-TWA 2 mg/m³ (respirable dust)

Skin notification N

Safe Work Australia (Australia, 4/2024)

TWA : 2 mg/m³ 8 hours. ⁸

Titanium Dioxide

OSHA

PEL-TWA 15¹²

Skin notification N¹²

NIOSH

Skin notification N¹²

ACGIH

TLV-TWA 10¹²

Skin notification N¹²

CAL/OSHA

PEL-TWA 10¹²
 Skin notification N¹²
 Safe Work Australia (Australia, 4/2024)
 TWA : 10 mg/m³ 8 hours. ⁸
styrene
 OSHA
 PEL-TWA 100 ppm⁷
 PEL-C 200 ppm; 600 ppm (Peak) for a single time period up to 5 min in any 3 hours
 Skin notification N
 NIOSH
 REL-TWA 50 ppm (215 mg/m³)
 REL-STEL 100 ppm (425 mg/m³)
 Skin notification N
 ACGIH
 TLV-TWA 20 ppm [1996]
 TLV-STEL 40 ppm [1996]
 Skin notification N
 CAL/OSHA
 PEL-TWA 50 ppm (215 mg/m³)
 PEL-STEL 100 ppm (425 mg/m³)
 PEL-C 500 ppm
 Skin notification Y
 Safe Work Australia (Australia, 4/2024)
 TWA : 20 ppm 8 hours. ⁸
 TWA : 85 mg/m³ 8 hours. ⁸
 STEL : 40 ppm 15 minutes. ⁸
 STEL : 170 mg/m³ 15 minutes. ⁸
 Provide adequate ventilation. Install local exhaust.

Appropriate engineering controls

Personal protective equipment

| | |
|--------------------------|--------------------------|
| Respiratory protection | Organic vapor respirator |
| Hand protection | Rubber gloves. Neoprene. |
| Eye protection | Safety goggle. |
| Skin and body protection | Wear suitable clothing |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|-------------------------------|
| Physical state | Paste |
| Colour | Yellow |
| Odour | Organic solvent |
| pH | Not available |
| Melting point/freezing point | Not available |
| Boiling point or initial boiling point and boiling range | 143.0 °C (289.4 °F) (styrene) |
| Flash point | 31.0 °C (87.8 °F) (styrene) |
| Flammability | Flammable |
| Lower and upper explosion limit/flammability limit | |
| Vapour pressure | 6 hPa at 20 °C (styrene) |
| Density and/or relative density | 1.6 - 1.75 g/cm ³ |
| Relative vapour density | |
| Solubility | Soluble in Organic solvent |
| Partition coefficient n-octanol/water (log value) | Not applicable |

| | |
|---------------------------|-------------------------------|
| Auto-ignition temperature | 490.0 °C (914.0 °F) (styrene) |
| Decomposition temperature | Not applicable |
| Viscosity | 135 - 140 KU at 30 °C |
| Particle characteristics | Not applicable |

10. STABILITY AND REACTIVITY

| | |
|-----------------------------------|--|
| Reactivity | Reacts violently with strong acids and strong oxidants |
| Chemical stability | Stable under normal storage and handling conditions |
| Possibility of hazardous reaction | Will not occur |
| Condition to avoid | High temperatures, sparks, open flame, and all other sources of ignition |
| Incompatible materials | Strong oxidizing agents, strong acids |
| Hazardous decomposition products | Not available |

11. TOXICOLOGICAL INFORMATION

| | |
|--|---|
| Acute toxicity (oral) | ATEmix = 4603.22 mg/kg (Category 5) Magnesium Dioxide LD50 (rat) oral = 3870.00 mg/kg Titanium Dioxide LD50 (rat) oral = 10000.00 mg/kg ¹⁰ styrene LD50 (rat) oral = 5000.00 mg/kg ² |
| Acute toxicity (dermal) | Not available |
| Acute toxicity (inhalation) | Not available |
| Skin corrosion and skin irritation | Causes skin irritation (styrene) |
| Serious eye damage or eye irritation | Causes serious eye irritation (styrene) |
| Respirator and skin sensitization | Not classified |
| Skin sensitization | Not classified |
| Germ cell mutagenicity | Not classified |
| Carcinogenicity | Not classified |
| Reproductive toxicity | Suspected of damaging fertility or the unborn child (styrene) |
| Specific target organ toxicity following single exposure | Not classified |
| Specific target organ toxicity following repeated exposure | Causes damage to organs through prolonged or repeated exposure (styrene) |
| Aspiration hazard | Not classified |

12. ECOLOGICAL INFORMATION

| | |
|-------------------------------|--|
| Acute aquatic hazard | Very toxic to aquatic life <u>Talcum powder</u> LC50 (fish) 96 hr = 0.089 mg/L ³ EC48 (shrimp) 48 hr = 0.00368 mg/L ErC-EC72 (Fungi) 96 hr = 0.007203 mg/L <u>Titanium Dioxide</u> EC48 (shrimp) 48 hr = 100 mg/L ¹⁰ ErC-EC72 (Fungi) 96 hr = 35.9 mg/L ¹⁰ <u>styrene</u> LC50 (fish) 96 hr = 9.1 mg/L EC48 (shrimp) 48 hr = 4.7 mg/L ErC-EC72 (Fungi) 96 hr = 0.72 mg/L |
| Long term aquatic hazard | No information |
| Persistence and degradability | Rapidly degradable (styrene) |
| Bioaccumulative potential | Bioaccumulative potential <u>styrene</u> log KOW = 2.95 BCF = 12-140 |
| Mobility in soil | The product is insoluble in water. If released to water, some of the components will have tendency to |

| | |
|-----------------------|--|
| Other adverse effects | evaporate while other components are expected to be highly mobile in soil and have the potential to reach underground water supplies. Not available |
|-----------------------|--|

13. DISPOSAL CONSIDERATIONS

| | |
|--------------------|--|
| Disposal methods | Disposing of this material/container should be done under all the regulations or handled by authorized waste collector in your country |
| Container disposal | Do not re-use empty containers |

14. TRANSPORT INFORMATION

Labels required



| | |
|----------------------------|----------------|
| UN number | 1263 |
| UN proper shipping name | Paint |
| Transport hazard class(es) | 3 |
| Packing group | III |
| Environmental hazards | Not applicable |
| Special precautions | Not applicable |
| Transport in bulk | Not applicable |

15. REGULATORY INFORMATION

| | |
|---|--|
| Inventory of existing chemical substance produced or imported in USA (TSCA) | All component in this product are listed |
| Toxic substance control act (TSCA) | All component in this product are listed |

16. OTHER INFORMATION

Issue date: 18 June 2025

References

- <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~tL93nR:1> (3-5-19)
- <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~lu5BAV:1> (03-05-19)
- <https://echa.europa.eu/brief-profile/-/briefprofile/100.035.328> (7/8/19)
- <https://echa.europa.eu/brief-profile/-/briefprofile/100.006.765> (3-5-19)
- <https://www.osha.gov/chemicaldata/chemResult.html?recNo=220> (3-5-19)
- <https://www.osha.gov/chemicaldata/chemResult.html?recNo=277> (7/8/19)
- <https://www.osha.gov/chemicaldata/chemResult.html?recNo=14> (7/8/19)
- Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (21-8-2024)
- Safe Work Australia Workplace exposure limits for airborne contaminants April 2024 (20-8-2024)
- <https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~Q1zAvm:3> (3-5-19)
- <https://echa.europa.eu/brief-profile/-/briefprofile/100.033.327> (3-5-19)
- <https://www.osha.gov/chemicaldata/chemResult.html?recNo=246> (3-5-19)
- <https://www.osha.gov/chemicaldata/chemResult.html?recNo=278> (17-12-19)