1. IDENTIFICATION OF THE MIXTU	JRE AND OF THE SUPPLIER
Product Identifier	
Product	Hardenner 2K Hi-Solid 2:1 (Fast dry) [21-07]
Recommended use of chemical	Use as Hardener in 2K paint
Restriction on use	No open flames, No spraks, and No smoking
Supplier's details	
Company	Big-Ben (Paints) Company Limited
Address	38 Mu 7 Suanluangruamjai Road Suanluang Krathumban Samutsakorn 74110 Thailand
Telephone number	+66 2 811 1442 or +66 2 811 1443
Fax number	+66 2 811 0632
E-mail	bbp@bbp.co.th
Emergency phone number	+66 2 811 1442 or + 66 2 811 1443
2. HAZARD IDENTIFICATION	
Classification of the substance or mi	
This product has been classified in a the information as required by the st	ccordance with the hazard communication standard 29 CSR 1910.1200; the SDS and labels contain all and
Flammable liquids	Category 1
Acute toxicity - dermal	Category 1
Skin corrosion/irritation	Category 3
Specific target organ toxicity (single	Category 3
exposure)	
Hazardous to the aquatic environment - acute hazard	Category 3
	of ingredient(s) of unknown dermal toxicity: 50.50% of ingredient(s) of unknown inhalation toxicity: 8.50%
Pictogram or symbol	
Signal word	Danger
Hazard statement:	
H224 Extremely flammable liquid	and vapour
H310 Fatal in contact with skin	
H316 Causes mild skin irritation	
H335 May cause respiratory irritat	ion
H336 May cause drowsiness or di	zziness
H402 Harmful to aquatic life	
Precautionary statement	
[PREVENTION]	
	ks / open flames / hot surfaces. No smoking.
P233 Keep container tightly closed	
P240 Ground / bond container and	
	al / ventilating / lighting / equipment.
P242 Use only non-sparking tools	
P243 Take precautionary measure	
P261 Avoid breathing dust / fume	
P262 Do not get in eyes, on skin,	or on ciotning.

P264 Wash thoroughly after handling.

P270 Do no eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

[RESPONSE]

P302+P350 IF ON SKIN Gently wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair) Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+P340 IF INHALED Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P310 Immediately call a POISON CENTER or doctor / physician.

P312 Call a POISON CENTER or doctor / physician if you feel unwell.

P322 Specific measures (see on this label).

P332+P313 IF skin irritation occursGet medical advice / attention.

P361 Remove / Take off immediately all contaminated clothing.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire Use dry sand, dry chemical or alcohol-resistant foam for extinction.

[STORAGE]

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

[DISPOSAL]

P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Content % (w/w)
1-METHOXY-2-PROPANOL ACETATE	108-65-6	1.05 - 1.91
Butyl Acetate	123-86-4	30.82 - 58.78
Homopolymer	28182-81-2	21.01 - 65.13
Homopolymer	53880-05-0	4.45 - 8.94
Xylene	1330-20-7	0.90 - 2.02

4. FIRST AND MEASURES

Inhalation	Remove to fresh air. If unconscious, place in recovery position and seek medical attention immediately.
Skin contact	Immediately flush with water for at least 15 minutes. Remove contaiminated clothing. Seek medical attention immediately. Wash thoroughly after handling.
Eye contact	Hold eyelids apart and immediately flush with plenty of water for 15 minutes. Seek medical advice. Remove contact lenses.
Ingestion	Rinse mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomitting unless directed to do so by medical personnel.
Most important symptoms/effects, acute and delayed	Dizziness. Drowsiness. Headache. Nausea. Vomitting. Weakness. Unconsciousness. Skin and eye redness. Pain. Nausea. Vomitting.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media	Dry chemical. Carbon Dioxide (CO ₂). Alcohol-resistant foam. Water spray.
Unsuitable extinguishing media	High volume water jet.
Specific hazards arising from the chemical	Flammable liquid. Vapors can form an ignitable misture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Container may rupture on heating.
Specific protective equipment and precautions for firefighters	Wear self-contained breathing apparatus and full protective clothing for firefighting.

6. ACCIDENTAL RELEASE MEAS	URES
Personal precautions, protective equipment, and emergency procedures	Keep unnecessary personnel away. Prevent further leakage or spillage if safe to do so. Use personal protective equipment. Use only non-sparkling tools.
Environmental precautions	Prevent the material from entering drains or water courses.
Methods and materials for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations.
7. HANDLING AND STORAGE	
Precautions for safe handling	Avoid breathing vapor and contact with eyes, skin, and clothing. Do no leave containers open. Avoid repeated or prolonged contact with skin.
Conditions for safe storage, including any incompatibilites	Keep away from heat or flames. Keep in cool, dry, ventilated storage and in closed containers. Store away from oxidizing agent.
8. EXPOSURE CONTROLS/PERS	DNAL PROTECTION
Control parameters	1-METHOXY-2-PROPANOL ACETATE OSHA PEL-TWA 50 ¹⁷ Skin notification Y ²⁰
	NIOSH REL-TWA 5 ¹⁷ Skin notification Y ¹⁷ ACGIH
	TLV-TWA 20 ¹⁷ Skin notification N ¹⁷ CAL/OSHA
	PEL-TWA 20 ¹⁷ Butyl Acetate OSHA
	PEL-TWA 150 ¹⁸ Skin notification N ²¹ NIOSH
	REL-TWA 150 ²¹ REL-STEL 200 ²¹ Skin notification N ²¹
	ACGIH TLV-TWA 50 ²¹ TLV-STEL 150 ²¹ Skin notification N
	CAL/OSHA PEL-TWA 150 ²¹ PEL-STEL 200 ²¹ Skin notification N ²¹ <u>Homopolymer</u> OSHA
	Skin notification NA ²² NIOSH
	Skin notification NA ²² ACGIH
	Skin notification NA ²² CAL/OSHA
	Skin notification NA ²² Homopolymer Xylene OSHA
	PEL-TWA 100 ¹⁹

	Skin notification N ¹⁹
	NIOSH
	REL-TWA 100 ¹⁹
	Skin notification N ¹⁹
	ACGIH TLV-TWA 100 ¹⁹
	TLV-TWA 100 ¹⁰ TLV-STEL 150 ¹⁹
	Skin notification N ¹⁹
	CAL/OSHA
	PEL-TWA 100 ¹⁹
	PEL-STEL 150 ¹⁹
	PEL-C 300 ¹⁹
	Skin notification N ¹⁹
Appropriate engineering controls	Provide adequate ventilation. Install local exhaust.
Personal protective equipment	
Respiratory protection	Organic vapor respirator
Hand protection	Rubber gloves. Neoprene.
Eye protection	Safety goggle.
Skin and body protection	Wear suitable clothing
9. PHYSICAL AND CHEMICAL PRO	PERTIES
Appearance	Liquid
Odor	Aromatic like
Odor threshold	Not Available
рН	Not Available
Melting point/freezing point	Not Available
Initial boiling point and boiling range	-
Flash point	23
Evaporation rate	Not Available
Flammability (solid, gas)	Not available
Upper/lower flammability or	Not available
explosive limits	Not available
Vapor pressure	Not Available
Vapor density	Not Available
Relative density	0.95 - 1.05 g/cm3
Solubility(ies)	Soluble in Aromatic solvent
Partition coefficient n-Octanol-water	Not Available
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
Viscosity	11-13 second by Ford cup No.4 @30 C
10. STABILITY AND REACTIVITY	
Reactivity	Reacts violently with strong acids and strong oxidants
Chemical stability	Stable under normal storage and handling conditions
Possibility of hazardous reaction	Will not occur
Condition to avoid	High temperatures, sparks, open flame, and all other sources of ignition
Incompatible materials	Strong oxidizing agents, strong acids
	Not available

11. TOXICOLOGICAL INFORMAT	ION
Acute toxicity (oral)	ATEmix = 10394.97 mg/kg (Not classified)
	1-METHOXY-2-PROPANOL ACETATE LD50 (rat) oral = 5155.00 mg/kg ⁶
	Butyl Acetate LD50 (rat) oral = 10736.00 mg/kg ⁷
Acute toxicity (dermal)	ATEmix = 16.50 mg/kg (Classify 1)
	1-METHOXY-2-PROPANOL ACETATE LD50 (rabbit) dermal = 2000.00 mg/kg ⁶
	Butyl Acetate LD50 (rabbit) dermal = 16.00 mg/kg ⁷
Acute toxicity (dermal)	ATEmix = 1435.93 mg/kg (Not classified)
	Butyl Acetate LC50 (rat) inhalation = 740.00 mg/kg ⁷
	Homopolymer LC50 (rat) inhalation = 9250.00 mg/kg ⁸
	Xylene LC50 (rat) inhalation = 6360.00 mg/kg ⁹
Skin corrosion and skin irritation	Causes mild skin irritation (Xylene)
Serious eye damage or eye	Not classified
irritation Respirator and skin sensitzation	Not classified
Skin sentization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity	May cause respiratory irritation (Butyl Acetate)
following single exposure	
Specific target organ toxicity	Not classified
following repeated exposure	
Aspiration hazard	Not classified

12. ECOLOGICAL INFORMATION	
Acute aquatic hazard	Harmful to aquatic life
	<u>1-METHOXY-2-PROPANOL ACETATE</u> LC50 (fish) 96 hr = 100 mg/L ⁶
	EC48 (shrimp) 48 hr = 50 mg/L ⁶
	$\frac{Butyl Acetate}{LC50 (fish) 96 hr} = 18 mg/L^7$
	EC48 (shrimp) 48 hr = 32 mg/L ⁷
	<u>Homopolymer</u> ErC-EC72 (Fungi) 96 hr = 1000 mg/L ^{undefined}
	<u>Xylene</u> LC50 (fish) 96 hr = 3.30 mg/L ¹²
Long term aquatic hazard	No information
Persistance and degradability	Rapidly degradable (1-METHOXY-2-PROPANOL ACETATE, Butyl Acetate, Xylene)
Bioaccumulative potential	Bioaccumulative potential <u>1-METHOXY-2-PROPANOL ACETATE</u> log KOW = 0.56 ²³
	BCF = 3^{23}
	$\frac{\text{Butyl Acetate}}{\text{log KOW} = 1.78^{24}}$
	$BCF = 7.00^{24}$
	$\frac{\text{Xylene}}{\text{log KOW}} = 3.20^{25}$
	BCF = 14.80 ²⁵
Mobility in soil	The product is insoluable in water. If released to water, some of the components will have tendency to
	evaporate while other components are expected to be highly mobile in soil and have the potential to
<u>Ollow</u>	reach underground water supplies.
Other adverse effects	Not available
13. DISPOSAL CONSIDERATIONS	
Disposal methods	Disposing of this material/container should be done under all the regulations or handled by authorized waste collector in your country
Container disposal	Do not re-use empty containers
14. TRANSPORT INFORMATION	
Labels required	
UN number	1263
UN proper shipping name	Paint
Transport hazard class(es)	3
Packing group	III
Environmental hazards	Not applicable
Special precautions	Not applicable
Transport in bulk	Not applicable
15. REGULATORY INFORMATION	
Inventory of existing chemical substance produced or imported in	All component in this product are listed
USA (TSCA)	
Toxic substance control act (TSCA)	All component in this product are listed

Issue date: 25 Augu	st 2022
References	
1. https://echa.euroj	pa.eu/brief-profile/-/briefprofile/100.101.969 (21-10-2020)
2. https://www.epa.ç	ovt.nz/database-search/chemical-classification-and-information-database-ccid/view/3377 (21-10-2020)
3. https://echa.euroj	pa.eu/brief-profile/-/briefprofile/100.002.116
4. https://www.osha	gov/chemicaldata/chemResult.html?recNo=748
5. N	
6. https://echa.euroj	pa.eu/brief-profile/-/briefprofile/100.003.277#ScientificProperties (17-12-19)
7. https://echa.euroj	pa.eu/brief-profile/-/briefprofile/100.004.236#ScientificProperties (17-12-19)
8. https://www.epa.ç	ovt.nz/database-search/chemical-classification-and-information-database-ccid/view/6025 (9-5-19)
9. https://www.epa.ç	ovt.nz/database-search/chemical-classification-and-information-database-ccid/view/682 (04-05-19)
10. https://echa.euro	ppa.eu/brief-profile/-/briefprofile/100.014.124 (24-12-19)
11. https://echa.euro	pa.eu/brief-profile/-/briefprofile/100.004.236 (04-05-19)
12. https://www.epa	govt.nz/database-search/chemical-classification-and-information-database-ccid/view/682 (04-05-19
13. https://echa.euro	ppa.eu/brief-profile/-/briefprofile/100.155.514 (9-5-19)
14. https://echa.euro	ppa.eu/brief-profile/-/briefprofile/100.003.277 (14/8/19)
15. https://echa.euro	ppa.eu/brief-profile/-/briefprofile/100.014.124 (04-05-19)
16. *	
17. https://www.osh	a.gov/chemicaldata/chemResult.html?recNo=130 (17-12-19)
18. www.oshhttps://	www.osha.gov/chemicaldata/chemResult.html?recNo=178 (17-12-19)a.gov
19. https://www.osh	a.gov/chemicaldata/chemResult.html?recNo=228 (04-05-19)
20. https://www.osh recNo=820 (03-05-1	ahttps://www.osha.gov/chemicaldata/chemResult.html?recNo=130 (17-12-19).gov/chemicaldata/chemResult.html? 9)
21. https://www.osh	a.gov/chemicaldata/chemResult.html?recNo=178 (17-12-19)
22. https://www.osh	a.gov/chemicaldata/chemResult.html?recNo=808 (9-5-19)
23. https://pubchem	ncbi.nlm.nih.gov/compound/7946#section=Environmental-Fate (03-05-19)
24. https://pubchem	ncbi.nlm.nih.gov/compound/31272#section=Environmental-Abiotic-Degradation (04-05-19)
25. https://pubchem	ncbi.nlm.nih.gov/compound/7929#section=Environmental-Fate (04-05-19)