1. IDENTIFICATION OF THE MIXTU	JRE AND OF THE SUPPLIER
Product Identifier	
Product	Hardener for 2K Primer 4:1 [21-20]
Recommended use of chemical	Use as Hardener in 2K paint
Restriction on use	No open flames, No spraks, and No smoking
Supplier's details	
Company	Big-Ben (Paints) Company Limited
Address	38 Mu 7 Suanluangruamjai Road Suanluang Krathumban Samutsakorn 74110 Thailand
Telephone number	+66 2 811 1442 or +66 2 811 1443
Fax number	+66 2 811 0632
E-mail	bbp@bbp.co.th
Emergency phone number	+66 2 811 1442 or + 66 2 811 1443
2. HAZARD IDENTIFICATION	·
Classification of the substance or mi This product has been classified in a the information as required by the st	accordance with the hazard communication standard 29 CSR 1910.1200; the SDS and labels contain all
Flammable liquids	Category 1
Acute toxicity - dermal	Category 1
Specific target organ toxicity (single exposure)	Category 3
Hazardous to the aquatic environment - acute hazard	Category 3
environment - acute nazaru	
GHS label elements Pictogram or symbol	of ingredient(s) of unknown inhalation toxicity: 0.00%
Signal word	Danger
Hazard statement:	
H224 Extremely flammable liquid	and vapour
H310 Fatal in contact with skin	
H335 May cause respiratory irritat	ion
H336 May cause drowsiness or di	zziness
H402 Harmful to aquatic life	
Precautionary statement	
[PREVENTION]	
	ks / open flames / hot surfaces. No smoking.
P233 Keep container tightly closed	
P240 Ground / bond container and	
	al / ventilating / lighting / equipment.
P242 Use only non-sparking tools	
P243 Take precautionary measure	
P261 Avoid breathing dust / fume / gas / mist / vapors / spray. P262 Do not get in eyes, on skin, or on clothing.	
P264 Wash thoroughly after handl	-
P270 Do no eat, drink or smoke when using this product.	
P271 Use only outdoors or in a well-ventilated area.	
	ell-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

[RESPONSE]

P302+P350 IF ON SKIN Gently wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair) Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+P340 IF INHALED Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P310 Immediately call a POISON CENTER or doctor / physician.

P312 Call a POISON CENTER or doctor / physician if you feel unwell.

P322 Specific measures (see on this label).

P361 Remove / Take off immediately all contaminated clothing.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire Use dry sand, dry chemical or alcohol-resistant foam for extinction.

### [STORAGE]

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

# [DISPOSAL]

P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS		
Chemical name	CAS No.	Content % (w/w)
Butyl Acetate	123-86-4	47.18 - 90.13
Homopolymer	28182-81-2	30.08 - 45.06

## 4. FIRST AND MEASURES

Inhalation	Remove to fresh air. If unconscious, place in recovery position and seek medical attention immediately.
Skin contact	Immediately flush with water for at least 15 minutes. Remove contaiminated clothing. Seek medical attention immediately. Wash thoroughly after handling.
Eye contact	Hold eyelids apart and immediately flush with plenty of water for 15 minutes. Seek medical advice. Remove contact lenses.
Ingestion	Rinse mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomitting unless directed to do so by medical personnel.
Most important symptoms/effects, acute and delayed	Dizziness. Drowsiness. Headache. Nausea. Vomitting. Weakness. Unconsciousness. Skin and eye redness. Pain. Nausea. Vomitting.

### 5. FIRE FIGHTING MEASURES

Suitable extinguishing media	Dry chemical. Carbon Dioxide (CO <sub>2</sub> ). Alcohol-resistant foam. Water spray.
Unsuitable extinguishing media	High volume water jet.
Specific hazards arising from the chemical	Flammable liquid. Vapors can form an ignitable misture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Container may rupture on heating.
Specific protective equipment and precautions for firefighters	Wear self-contained breathing apparatus and full protective clothing for firefighting.

6. ACCIDENTAL RELEASE MEASURES	
Personal precautions, protective equipment, and emergency procedures	Keep unnecessary personnel away. Prevent further leakage or spillage if safe to do so. Use personal protective equipment. Use only non-sparkling tools.
Environmental precautions	Prevent the material from entering drains or water courses.
Methods and materials for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations.

7. HANDLING AND STORAGE	
Precautions for safe handling	Avoid breathing vapor and contact with eyes, skin, and clothing. Do no leave containers open. Avoid
	repeated or prolonged contact with skin.
Conditions for safe storage,	Keep away from heat or flames. Keep in cool, dry, ventilated storage and in closed
including any incompatibilites	containers. Store away from oxidizing agent.
8. EXPOSURE CONTROLS/PERS	ONAL PROTECTION
Control parameters	Butyl Acetate OSHA
	PEL-TWA 150 <sup>22</sup>
	Skin notification N <sup>23</sup> NIOSH
	REL-TWA 150 <sup>23</sup>
	REL-STEL 200 <sup>23</sup>
	Skin notification N <sup>23</sup> ACGIH
	TLV-TWA 50 <sup>23</sup>
	TLV-STEL 150 <sup>23</sup>
	Skin notification N CAL/OSHA
	PEL-TWA 150 <sup>23</sup>
	PEL-STEL 200 <sup>23</sup>
	Skin notification N <sup>23</sup>
	Homopolymer OSHA
	Skin notification NA <sup>24</sup>
	NIOSH
	Skin notification NA <sup>24</sup> ACGIH
	Skin notification NA <sup>24</sup>
	CAL/OSHA
	Skin notification NA <sup>24</sup>
Appropriate engineering controls	Provide adequate ventilation. Install local exhaust.
Personal protective equipment	
Respiratory protection	Organic vapor respirator
Hand protection	Rubber gloves. Neoprene.
Eye protection	Safety goggle.
Skin and body protection	Wear suitable clothing

9. PHYSICAL AND CHEMICAL PRO	9. PHYSICAL AND CHEMICAL PROPERTIES	
Appearance	Liquid	
Odor	Organic solvent	
Odor threshold	Not Available	
pH	Not Available	
Melting point/freezing point	Not available	
Initial boiling point and boiling range	Not available	
Flash point	< 23	
Evaporation rate	Not Available	
Flammability (solid, gas)	Not Available	
Upper/lower flammability or	Not Available	
explosive limits	Not Available	
Vapor pressure	Not Available	
Vapor density	Not Available	
Relative density	0.91-1.01	
Solubility(ies)	Soluble in Organic solvent	
Partition coefficient n-Octanol-water	Not Available	
Auto-ignition temperature	Not Available	
Decomposition temperature	Not Available	
Viscosity	8-12 sec/F4@30c	
10. STABILITY AND REACTIVITY		
Reactivity	Reacts violently with strong acids and strong oxidants	
Chemical stability	Stable under normal storage and handling conditions	
Possibility of hazardous reaction	Will not occur	
Condition to avoid	High temperatures, sparks, open flame, and all other sources of ignition	
Incompatible materials	Strong oxidizing agents, strong acids	
Hazardous decomposition products	Not available	

11. TOXICOLOGICAL INFORMATION	
Acute toxicity (oral)	ATEmix = 10736.00 mg/kg (Not classified)
	Butyl Acetate LD50 (rat) oral = 10736.00 mg/kg <sup>18</sup>
Acute toxicity (dermal)	ATEmix = 16.00 mg/kg (Classify 1)
	Butyl Acetate LD50 (rabbit) dermal = 16.00 mg/kg <sup>18</sup>
Acute toxicity (dermal)	ATEmix = 1170.89 mg/kg (Not classified)
	Butyl Acetate LC50 (rat) inhalation = 740.00 mg/kg <sup>18</sup>
	Homopolymer LC50 (rat) inhalation = 9250.00 mg/kg <sup>19</sup>
Skin corrosion and skin irritation	Not classified
Serious eye damage or eye irritation	Not classified
Respirator and skin sensitzation	Not classified
Skin sentization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity following single exposure	May cause respiratory irritation (Butyl Acetate)
Specific target organ toxicity following repeated exposure	Not classified
Aspiration hazard	Not classified
12. ECOLOGICAL INFORMATION	N Contraction of the second seco
Acute aquatic hazard	Harmful to aquatic life
	$\frac{Butyl Acetate}{LC50 (fish) 96 hr} = 18 mg/L^{18}$
	EC48 (shrimp) 48 hr = 32 mg/L <sup>18</sup>
	<u>Homopolymer</u> ErC-EC72 (Fungi) 96 hr = 1000 mg/L <sup>undefined</sup>
Long term aquatic hazard	No information
Persistance and degradability	Rapidly degradable (Butyl Acetate)
Bioaccumulative potential	Bioaccumulative potential <u>Butyl Acetate</u> log KOW = 1.78 <sup>25</sup>
	BCF = 7.00 <sup>25</sup>
Mobility in soil	The product is insoluable in water. If released to water, some of the components will have tendency to
	evaporate while other components are expected to be highly mobile in soil and have the potential to reach underground water supplies.
Other adverse effects	Not available
13. DISPOSAL CONSIDERATION	
Disposal methods	Disposing of this material/container should be done under all the regulations or handled by authorized
•	waste collector in your country
Container disposal	Do not re-use empty containers

# 14. TRANSPORT INFORMATION

14. TRANSPORT INFORMATION	
Labels required	
UN number	1263
UN proper shipping name	Paint
Transport hazard class(es)	3
Packing group	III
Environmental hazards	Not applicable
Special precautions	Not applicable
Transport in bulk	Not applicable
15. REGULATORY INFORMATION	
Inventory of existing chemical substance produced or imported in USA (TSCA)	All component in this product are listed
Toxic substance control act (TSCA)	All component in this product are listed
16. OTHER INFORMATION	
Issue date: 25 August 2022	
References	
1. https://toxnet.nlm.nih.gov/cgi-bin/s	is/search2/f?./temp/~pB0xAg:1 (3-5-19)
2. https://toxnet.nlm.nih.gov/cgi-bin/s	is/search2/f?./temp/~VMFBmI:3 (3-5-19)
3. https://www.epa.govt.nz/database	-search/chemical-classification-and-information-database-ccid/view/682 (04-05-19)
4. https://echa.europa.eu/brief-profile	e/-/briefprofile/100.003.297 (3-5-19)
5. https://echa.europa.eu/brief-profile	e/-/briefprofile/100.014.124 (24-12-19)
6. https://echa.europa.eu/brief-profile	e/-/briefprofile/100.000.683 (3-5-19)
7. https://echa.europa.eu/brief-profile	e/-/briefprofile/100.003.297
8. https://toxnet.nlm.nih.gov/cgi-bin/s	is/search2/f?./temp/~lQhZ8l:1 (03-05-19)
9. https://www.epa.govt.nz/database	-search/chemical-classification-and-information-database-ccid/view/682 (04-05-19
10. https://echa.europa.eu/brief-profi	le/-/briefprofile/100.003.297 (03-05-19)
11. https://echa.europa.eu/brief-profi	le/-/briefprofile/100.014.124 (04-05-19)
12. https://www.osha.gov/chemicaldata/chemResult.html?recNo=490 (3-5-19)	
13. https://www.osha.gov/chemicaldata/chemResult.html?recNo=89 (03-05-19)	
14. https://www.osha.gov/chemicalda	ata/chemResult.html?recNo=228 (04-05-19)
15. https://pubchem.ncbi.nlm.nih.gov/compound/263#section=Octanol-Water-Partition-Coefficient (3-5-19)	
16. https://pubchem.ncbi.nlm.nih.gov/compound/1140#section=Environmental-Fate (03-05-19)	
17. https://pubchem.ncbi.nlm.nih.gov/compound/7929#section=Environmental-Fate (04-05-19)	
18. https://echa.europa.eu/brief-profi	le/-/briefprofile/100.004.236#ScientificProperties (17-12-19)
19. https://www.epa.govt.nz/databas	e-search/chemical-classification-and-information-database-ccid/view/6025 (9-5-19)
20. https://echa.europa.eu/brief-profi	le/-/briefprofile/100.004.236 (04-05-19)
21. https://echa.europa.eu/brief-profile/-/briefprofile/100.155.514 (9-5-19)	
22. www.oshhttps://www.osha.gov/cl	nemicaldata/chemResult.html?recNo=178 (17-12-19)a.gov
23. https://www.osha.gov/chemicaldata/chemResult.html?recNo=178 (17-12-19)	
24. https://www.osha.gov/chemicaldata/chemResult.html?recNo=808 (9-5-19)	
25. https://pubchem.ncbi.nlm.nih.gov/compound/31272#section=Environmental-Abiotic-Degradation (04-05-19)	