

1. IDENTIFICATION OF THE MIXTURE AND OF THE SUPPLIER	
Product Identifier	
Product	Automotive Nitrocellulose Clearcoat [30-8008]
Recommended use of chemical	Use as Coating
Restriction on use	No open flames, No spraks, and No smoking
Supplier's details	
Company	Big-Ben (Paints) Company Limited
Address	38 Mu 7 Suanluangruamjai Road Suanluang Krathumban Samutsakorn 74110 Thailand
Telephone number	+66 2 811 1442 or +66 2 811 1443
Fax number	+66 2 811 0632
E-mail	bbp@bbp.co.th
Emergency phone number	+66 2 811 1442 or + 66 2 811 1443

2. HAZARD IDENTIFICATION	
Classification of the substance or mixture This product has been classified in accordance with the hazard communication standard 29 CSR 1910.1200; the SDS and labels contain all the information as required by the standard.	
Flammable liquids	Category 1
Acute toxicity - oral	Category 5
Acute toxicity - dermal	Category 2
Skin corrosion/irritation	Category 2
Eye damage/irritation	Category 2A
Sentization - respiratory	Category 1
Toxic to reproduction	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration hazard	Category 1
Hazardous to the aquatic environment - acute hazard	Category 3
Remark: Percentage of mixture consisting of ingredient(s) of unknown oral toxicity: 42.35% Percentage of mixture consisting of ingredient(s) of unknown dermal toxicity: 46.87% Percentage of mixture consisting of ingredient(s) of unknown inhalation toxicity: 72.56%	

GHS label elements	
Pictogram or symbol	
Signal word	Danger

Hazard statement: H224 Extremely flammable liquid and vapour H303 May be harmful if swallowed H304 May be fatal if swallowed and enters airways H310 Fatal in contact with skin H315 Causes skin irritation H319 Causes serious eye irritation H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled H335 May cause respiratory irritation H336 May cause drowsiness or dizziness	
--	--

H361 Suspected of damaging fertility or the unborn child
H373 May cause damage to organs through prolonged or repeated exposure
H402 Harmful to aquatic life

Precautionary statement

[PREVENTION]

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat / sparks / open flames / hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground / bond container and receiving equipment.
P241 Use explosion-proof electrical / ventilating / lighting / equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust / fume / gas / mist / vapors / spray.
P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
P262 Do not get in eyes, on skin, or on clothing.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves / protective clothing / eye protection / face protection.
P285 In case of inadequate ventilation wear respiratory protection.

[RESPONSE]

P301+P310 IF SWALLOWED Immediately call a POISON CENTER or doctor / physician.
P302+P350 IF ON SKIN Gently wash with plenty of soap and water.
P302+P352 IF ON SKIN Wash with plenty of soap and water.
P303+P361+P353 IF ON SKIN (or hair) Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
P304+P340 IF INHALED Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P304+P341 IF INHALED If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned Get medical advice / attention.
P310 Immediately call a POISON CENTER or doctor / physician.
P312 Call a POISON CENTER or doctor / physician if you feel unwell.
P314 Get medical advice / attention if you feel unwell.
P321 Specific treatment (see on this label).
P322 Specific measures (see on this label).
P331 Do NOT induce vomiting.
P332+P313 IF skin irritation occurs Get medical advice / attention.
P337+P313 IF eye irritation persists Get medical advice / attention.
P342+P311 IF experiencing respiratory symptoms Call a POISON CENTER or doctor / physician.
P361 Remove / Take off immediately all contaminated clothing.
P362 Take off contaminated clothing and wash before reuse.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire Use dry sand, dry chemical or alcohol-resistant foam for extinction.

[STORAGE]

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

[DISPOSAL]

P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS		
Chemical name	CAS No.	Content % (w/w)
1-ACETOXY-2-ETHOXYETHANE	111-15-9	1.71 - 3.60
1-Butanol	71-36-3	3.81 - 6.01
1-benzyl 2-butyl benzene-1,2-dicarboxylate	85-68-7	3.89 - 5.54
2-BUTOXYETHANOL	111-76-2	2.06 - 6.26
2-PROPANOL	67-63-0	1.86 - 5.15
4-Methyl-2-pentanone	108-10-1	5.30 - 13.97
Acetone	67-64-1	2.04 - 3.14
Acrylic resin	-	14.88 - 24.46
Butyl Acetate	123-86-4	4.28 - 7.91
Cellulose nitrate	9004-70-1	7.06 - 11.01
Melamine Polymer	-	1.12 - 2.75
Toluene	108-88-3	12.66 - 41.64

4. FIRST AND MEASURES	
Inhalation	Remove to fresh air. If unconscious, place in recovery position and seek medical attention immediately.
Skin contact	Immediately flush with water for at least 15 minutes. Remove contaminated clothing. Seek medical attention immediately. Wash thoroughly after handling.
Eye contact	Hold eyelids apart and immediately flush with plenty of water for 15 minutes. Seek medical advice. Remove contact lenses.
Ingestion	Rinse mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.
Most important symptoms/effects, acute and delayed	Dizziness. Drowsiness. Headache. Nausea. Vomiting. Weakness. Unconsciousness. Skin and eye redness. Pain. Nausea. Vomiting.

5. FIRE FIGHTING MEASURES	
Suitable extinguishing media	Dry chemical. Carbon Dioxide (CO ₂). Alcohol-resistant foam. Water spray.
Unsuitable extinguishing media	High volume water jet.
Specific hazards arising from the chemical	Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Container may rupture on heating.
Specific protective equipment and precautions for firefighters	Wear self-contained breathing apparatus and full protective clothing for firefighting.

6. ACCIDENTAL RELEASE MEASURES	
Personal precautions, protective equipment, and emergency procedures	Keep unnecessary personnel away. Prevent further leakage or spillage if safe to do so. Use personal protective equipment. Use only non-sparkling tools.
Environmental precautions	Prevent the material from entering drains or water courses.
Methods and materials for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations.

7. HANDLING AND STORAGE	
Precautions for safe handling	Avoid breathing vapor and contact with eyes, skin, and clothing. Do not leave containers open. Avoid repeated or prolonged contact with skin.
Conditions for safe storage, including any incompatibilities	Keep away from heat or flames. Keep in cool, dry, ventilated storage and in closed containers. Store away from oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION	
Control parameters	<u>1-ACETOXY-2-ETHOXYETHANE</u>

OSHA
PEL-TWA 100⁴¹
Skin notification Y⁴¹
NIOSH
REL-TWA 0.5⁴¹
Skin notification Y⁴¹
ACGIH
TLV-TWA 5⁴¹
Skin notification Y⁴¹
CAL/OSHA
PEL-TWA 5⁴¹
Skin notification Y⁴¹
1-Butanol
OSHA
PEL-TWA 100 ppm (300 mg/m³)²¹
Skin notification N²¹
NIOSH
REL-C 50 ppm (150 mg/m³)²¹
Skin notification Y²¹
ACGIH
TLV-TWA 20 ppm [1998]²¹
Skin notification N²¹
CAL/OSHA
PEL-C 50 ppm (150 mg/m³)²¹
Skin notification Y²¹
1-benzyl 2-butyl benzene-1,2-dicarboxylate
2-BUTOXYETHANOL
OSHA
PEL-TWA 50⁴²
Skin notification Y⁴²
NIOSH
REL-TWA 5⁴²
Skin notification Y⁴²
ACGIH
TLV-TWA 20⁴²
Skin notification N⁴²
CAL/OSHA
PEL-TWA 20⁴²
Skin notification Y⁴²
2-PROPANOL
OSHA
PEL-TWA 400²²
Skin notification N²²
NIOSH
REL-TWA 400²²
REL-STEL 500²²
Skin notification N²²
ACGIH
TLV-TWA 200²²
TLV-STEL 400²²
4-Methyl-2-pentanone
OSHA
PEL-TWA 100²³
Skin notification N²³
NIOSH
REL-TWA 50²³
REL-STEL 75²³

Skin notification N²³
 ACGIH
 TLV-TWA 20²³
 TLV-STEL 75²³
 Skin notification N²³
 CAL/OSHA
 PEL-TWA 50²³
 PEL-STEL 75²³
 Skin notification N²³
Acetone
 OSHA
 PEL-TWA 1000²⁴
 Skin notification N²⁴
 NIOSH
 REL-TWA 250²⁴
 Skin notification N²⁴
 ACGIH
 TLV-TWA 2500²⁴
 TLV-STEL 500²⁴
 Skin notification N²⁴
 CAL/OSHA
 PEL-TWA 500²⁴
 PEL-STEL 750²⁴
 PEL-C 3000²⁴
 Skin notification N²⁴
Acrylic resin
Butyl Acetate
 OSHA
 PEL-TWA 150²⁵
 Skin notification N²⁸
 NIOSH
 REL-TWA 150²⁸
 REL-STEL 200²⁸
 Skin notification N²⁸
 ACGIH
 TLV-TWA 50²⁸
 TLV-STEL 150²⁸
 Skin notification N
 CAL/OSHA
 PEL-TWA 150²⁸
 PEL-STEL 200²⁸
 Skin notification N²⁸
Cellulose nitrate
Melamine Polymer
Toluene
 OSHA
 PEL-TWA 200 ppm²⁶
 PEL-C 300 ppm; 500 ppm (Peak) [10 min maximum in an 8 hr shift]²⁶
 Skin notification N²⁶
 NIOSH
 REL-TWA 100 ppm (375 mg/m³)²⁶
 REL-STEL 150 ppm (560 mg/m³)²⁶
 Skin notification N²⁶
 ACGIH
 TLV-TWA 20 ppm [2006]²⁶
 Skin notification N²⁶
 CAL/OSHA

	PEL-TWA 10 ppm (37 mg/m ³) ²⁶ PEL-STEL 150 ppm (560 mg/m ³) ²⁶ PEL-C 500 ppm ²⁶ Skin notification Y ²⁶
Appropriate engineering controls	Provide adequate ventilation. Install local exhaust.
Personal protective equipment	
Respiratory protection	Organic vapor respirator
Hand protection	Rubber gloves. Neoprene.
Eye protection	Safety goggle.
Skin and body protection	Wear suitable clothing


9. PHYSICAL AND CHEMICAL PROPERTIES	
Appearance	High viscosity liquid
Odor	Organic Solvent
Odor threshold	Not available
pH	Not available
Melting point/freezing point	Not Available
Initial boiling point and boiling range	Not Available
Flash point	<23
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Upper/lower flammability or explosive limits	Not available Not available
Vapor pressure	Not available
Vapor density	Not available
Relative density	0.98-0.99
Solubility(ies)	Soluble in organic solvent
Partition coefficient n-Octanol-water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	16-18 second by ford cup No. 4

10. STABILITY AND REACTIVITY	
Reactivity	Reacts violently with strong acids and strong oxidants
Chemical stability	Stable under normal storage and handling conditions
Possibility of hazardous reaction	Will not occur
Condition to avoid	High temperatures, sparks, open flame, and all other sources of ignition
Incompatible materials	Strong oxidizing agents, strong acids
Hazardous decomposition products	Not available

11. TOXICOLOGICAL INFORMATION	
Acute toxicity (oral)	<p>ATEmix = 2160.73 mg/kg (Category 5)</p> <p>1-ACETOXY-2-ETHOXYETHANE LD50 (rat) oral = 2900.00 mg/kg³⁵</p> <p>1-Butanol LD50 (rat) oral = 790.00 mg/kg²</p> <p>1-benzyl 2-butyl benzene-1,2-dicarboxylate LD50 (rat) oral = 2330.00 mg/kg³⁶</p> <p>2-BUTOXYETHANOL LD50 (rat) oral = 470.00 mg/kg³⁷</p> <p>2-PROPANOL LD50 (rat) oral = 4710.00 mg/kg³</p> <p>Acetone LD50 (rat) oral = 5800.00 mg/kg⁴</p> <p>Butyl Acetate LD50 (rat) oral = 10736.00 mg/kg⁵</p> <p>Toluene LD50 (rat) oral = 5000.00 mg/kg⁶</p>
Acute toxicity (dermal)	<p>ATEmix = 145.47 mg/kg (Classify 2)</p> <p>1-ACETOXY-2-ETHOXYETHANE LD50 (rabbit) dermal = 10300.00 mg/kg³⁵</p> <p>1-Butanol LD50 (rabbit) dermal = 3400.00 mg/kg²</p> <p>2-BUTOXYETHANOL LD50 (rabbit) dermal = 400.00 mg/kg³⁷</p> <p>2-PROPANOL LD50 (rabbit) dermal = 12870.00 mg/kg³</p> <p>Acetone LD50 (rabbit) dermal = 7426.00 mg/kg⁴</p> <p>Butyl Acetate LD50 (rabbit) dermal = 16.00 mg/kg⁵</p> <p>Toluene LD50 (rabbit) dermal = 14100.00 mg/kg⁶</p>
Acute toxicity (dermal)	<p>ATEmix = 26.84 mg/kg (Not classified)</p> <p>1-Butanol LC50 (rat) inhalation = 8000.00 mg/kg²</p> <p>2-PROPANOL LC50 (rat) inhalation = 72.60 mg/kg³</p> <p>4-Methyl-2-pentanone LC50 (rat) inhalation = 11.60 mg/kg⁷</p> <p>Acetone LC50 (rat) inhalation = 76.00 mg/kg⁴</p> <p>Butyl Acetate LC50 (rat) inhalation = 740.00 mg/kg⁵</p>
Skin corrosion and skin irritation	Causes skin irritation (2-BUTOXYETHANOL,Toluene)
Serious eye damage or eye irritation	Causes serious eye irritation (1-Butanol,2-BUTOXYETHANOL,2-PROPANOL,4-Methyl-2-pentanone ,Acetone)
Respirator and skin sensitization	May cause allergy or asthma symptoms or breathing difficulties if inhaled (1-Butanol)
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Suspected of damaging fertility or the unborn child (Toluene)
Specific target organ toxicity following single exposure	May cause respiratory irritation (1-Butanol,2-PROPANOL,4-Methyl-2-pentanone ,Acetone,Butyl Acetate,Toluene)
Specific target organ toxicity following repeated exposure	May cause damage to organs through prolonged or repeated exposure (Toluene)
Aspiration hazard	May be fatal if swallowed and enters airways (Toluene)

12. ECOLOGICAL INFORMATION	
Acute aquatic hazard	<p>Harmful to aquatic life</p> <p><u>1-ACETOXY-2-ETHOXYETHANE</u> LC50 (fish) 96 hr = 40 mg/L³⁹</p> <p><u>1-Butanol</u> LC50 (fish) 96 hr = 100 mg/L²</p> <p>EC48 (shrimp) 48 hr = 1983 mg/L²</p> <p><u>2-BUTOXYETHANOL</u> LC50 (fish) 96 hr = 1474 mg/L⁴⁰</p> <p>EC48 (shrimp) 48 hr = 1500 mg/L⁴⁰</p> <p><u>2-PROPANOL</u> LC50 (fish) 96 hr = 6120 mg/L³</p> <p><u>4-Methyl-2-pentanone</u> LC50 (fish) 96 hr = 179 mg/L¹²</p> <p>EC48 (shrimp) 48 hr = 200 mg/L¹²</p> <p><u>Acetone</u> LC50 (fish) 96 hr = 4740 mg/L⁴</p> <p><u>Butyl Acetate</u> LC50 (fish) 96 hr = 18 mg/L⁵</p> <p>EC48 (shrimp) 48 hr = 32 mg/L⁵</p> <p><u>Toluene</u> LC50 (fish) 96 hr = 7.3 mg/L¹⁶</p> <p>EC48 (shrimp) 48 hr = 6 mg/L¹⁶</p> <p>ErC-EC72 (Fungi) 96 hr = 12.5 mg/L¹⁶</p>
Long term aquatic hazard	No information
Persistence and degradability	Rapidly degradable (4-Methyl-2-pentanone ,Acetone,Butyl Acetate,Toluene)
Bioaccumulative potential	<p>Bioaccumulative potential</p> <p><u>1-ACETOXY-2-ETHOXYETHANE</u> log KOW = 0.24⁴³</p> <p>BCF = 3⁴³</p> <p><u>1-Butanol</u> log KOW = 0.88²⁹</p> <p>BCF = 3²⁹</p> <p><u>1-benzyl 2-butyl benzene-1,2-dicarboxylate</u> log KOW = 4.84 @ 20 °C³⁶</p> <p><u>2-BUTOXYETHANOL</u> log KOW = 0.83⁴⁴</p> <p>BCF = 3⁴⁴</p> <p><u>4-Methyl-2-pentanone</u> log KOW = 1.31³⁰</p> <p>BCF = 3³⁰</p> <p><u>Acetone</u> log KOW = -0.24³¹</p> <p>BCF = 0.69³¹</p> <p><u>Butyl Acetate</u> log KOW = 1.78³²</p> <p>BCF = 7.00³²</p> <p><u>Toluene</u> log KOW = 2.73³³</p> <p>BCF = 13³³</p>
Mobility in soil	The product is insoluble in water. If released to water, some of the components will have tendency to evaporate while other components are expected to be highly mobile in soil and have the potential to reach underground water supplies.
Other adverse effects	Not available

13. DISPOSAL CONSIDERATIONS	
Disposal methods	Disposing of this material/container should be done under all the regulations or handled by authorized waste collector in your country
Container disposal	Do not re-use empty containers

14. TRANSPORT INFORMATION	
Labels required	
UN number	1263
UN proper shipping name	Paint
Transport hazard class(es)	3
Packing group	III
Environmental hazards	Not applicable
Special precautions	Not applicable
Transport in bulk	Not applicable

15. REGULATORY INFORMATION	
Inventory of existing chemical substance produced or imported in USA (TSCA)	All component in this product are listed
Toxic substance control act (TSCA)	All component in this product are listed

16. OTHER INFORMATION	
Issue date: 25 August 2022	
References	
1. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~JDD7dD:1 (31-05-19)	
2. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~pB0xAg:1 (3-5-19)	
3. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~yPvzP0:1 (3-5-19)	
4. https://echa.europa.eu/brief-profile/-/briefprofile/100.000.602 (23-12-19)	
5. https://echa.europa.eu/brief-profile/-/briefprofile/100.004.236#ScientificProperties (17-12-19)	
6. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~VMFBml:3 (3-5-19)	
7. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.228 (17-12-19)	
8. https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/682 (04-05-19)	
9. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.297 (3-5-19)	
10. https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124 (24-12-19)	
11. https://echa.europa.eu/brief-profile/-/briefprofile/100.000.683 (3-5-19)	
12. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.228	
13. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.297	
14. https://echa.europa.eu/brief-profile/-/briefprofile/100.000.601 (3-5-19)	
15. https://echa.europa.eu/brief-profile/-/briefprofile/100.004.236 (04-05-19)	
16. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~IQhZ8l:1 (03-05-19)	
17. https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/682 (04-05-19)	
18. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.297 (03-05-19)	
19. https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124 (04-05-19)	
20. https://www.osha.gov/chemicaldata/chemResult.html?recNo=176 (31-05-19)	
21. https://www.osha.gov/chemicaldata/chemResult.html?recNo=490 (3-5-19)	
22. https://www.osha.gov/chemicaldata/chemResult.html?recNo=475 (3-5-19)	
23. https://www.osha.gov/chemicaldata/chemResult.html?recNo=75	

24. https://www.osha.gov/chemicaldata/chemResult.html?recNo=476 (23-12-19)
25. www.oshhttps://www.osha.gov/chemicaldata/chemResult.html?recNo=178 (17-12-19)a.gov
26. https://www.osha.gov/chemicaldata/chemResult.html?recNo=89 (03-05-19)
27. https://www.osha.gov/chemicaldata/chemResult.html?recNo=228 (04-05-19)
28. https://www.osha.gov/chemicaldata/chemResult.html?recNo=178 (17-12-19)
29. https://pubchem.ncbi.nlm.nih.gov/compound/263#section=Octanol-Water-Partition-Coefficient (3-5-19)
30. https://pubchem.ncbi.nlm.nih.gov/compound/7909#section=Octanol-Water-Partition-Coefficient
31. https://pubchem.ncbi.nlm.nih.gov/compound/180 (23-12-19)
32. https://pubchem.ncbi.nlm.nih.gov/compound/31272#section=Environmental-Abiotic-Degradation (04-05-19)
33. https://pubchem.ncbi.nlm.nih.gov/compound/1140#section=Environmental-Fate (03-05-19)
34. https://pubchem.ncbi.nlm.nih.gov/compound/7929#section=Environmental-Fate (04-05-19)
35. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~m8awRK:3 (3-5-19)
36. https://echa.europa.eu/brief-profile/-/briefprofile/100.001.475 (17-4-20)
37. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~lQIQFd:1 (03-05-19)
38. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.550 (03-05-19)
39. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~7TG1XJ:1 (03-05-19)
40. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.550#ScientificProperties (17-12-19)
41. https://www.osha.gov/chemicaldata/chemResult.html?recNo=122 (3-5-19)
42. https://www.osha.gov/chemicaldata/chemResult.html?recNo=130 (03-05-19)
43. https://pubchem.ncbi.nlm.nih.gov/compound/8095#section=Environmental-Fate-Exposure-Summary (03-05-19)
44. https://pubchem.ncbi.nlm.nih.gov/compound/8133#section=Environmental-Abiotic-Degradation (03-05-19)