


1. IDENTIFICATION OF THE MIXTURE AND OF THE SUPPLIER	
Product Identifier	
Product	Heavy Polyester Putty RGB with hardener [83-4001]
Recommended use of chemical	Use as putty direct to metal
Restriction on use	No open flames, No spraks, and No smoking
Supplier's details	
Company	Big-Ben (Paints) Company Limited
Address	38 Mu 7 Suanluangruamjai Road Suanluang Krathumban Samutsakorn 74110 Thailand
Telephone number	+66 2 811 1442 or +66 2 811 1443
Fax number	+66 2 811 0632
E-mail	bbp@bbp.co.th
Emergency phone number	+66 2 811 1442 or + 66 2 811 1443

2. HAZARD IDENTIFICATION	
Classification of the substance or mixture This product has been classified in accordance with the hazard communication standard 29 CSR 1910.1200; the SDS and labels contain all the information as required by the standard.	
Flammable liquids	Category 1
Skin corrosion/irritation	Category 2
Eye damage/irritation	Category 2A
Toxic to reproduction	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Hazardous to the aquatic environment - acute hazard	Category 1
Remark: Percentage of mixture consisting of ingredient(s) of unknown oral toxicity: 62.38% Percentage of mixture consisting of ingredient(s) of unknown dermal toxicity: 99.59% Percentage of mixture consisting of ingredient(s) of unknown inhalation toxicity: 99.59%	
GHS label elements	
Pictogram or symbol	
Signal word	Danger

Hazard statement: H224 Extremely flammable liquid and vapour H315 Causes skin irritation H319 Causes serious eye irritation H361 Suspected of damaging fertility or the unborn child H372 Causes damage to organs through prolonged or repeated exposure H400 Very toxic to aquatic life	
Precautionary statement [PREVENTION] P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat / sparks / open flames / hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground / bond container and receiving equipment. P241 Use explosion-proof electrical / ventilating / lighting / equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge.	

P260 Do not breathe dust / fume / gas / mist / vapors / spray.
P264 Wash thoroughly after handling.
P270 Do no eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P280 Wear protective gloves / protective clothing / eye protection / face protection.

[RESPONSE]

P302+P352 IF ON SKIN Wash with plenty of soap and water.
P303+P361+P353 IF ON SKIN (or hair) Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
P305+P351+P338 IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned Get medical advice / attention.
P314 Get medical advice / attention if you feel unwell.
P321 Specific treatment (see on this label).
P332+P313 IF skin irritation occurs Get medical advice / attention.
P337+P313 IF eye irritation persists Get medical advice / attention.
P362 Take off contaminated clothing and wash before reuse.
P370+P378 In case of fire Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P391 Collect spillage.

[STORAGE]

P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

[DISPOSAL]

P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Content % (w/w)
Calcium carbonate	471-34-1	15.46 - 36.36
Talcum powder	14807-96-6	31.48 - 64.86
Unsaturated polyester resin	64386-67-0	19.37 - 32.56
styrene	100-42-5	5.09 - 14.41
Others	-	0.01 - 0.01

4. FIRST AND MEASURES

Inhalation	Remove to fresh air. If unconscious, place in recovery position and seek medical attention immediately.
Skin contact	Immediately flush with water for at least 15 minutes. Remove contaminated clothing. Seek medical attention immediately. Wash thoroughly after handling.
Eye contact	Hold eyelids apart and immediately flush with plenty of water for 15 minutes. Seek medical advice. Remove contact lenses.
Ingestion	Rinse mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.
Most important symptoms/effects, acute and delayed	Dizziness. Drowsiness. Headache. Nausea. Vomiting. Weakness. Unconsciousness. Skin and eye redness. Pain. Nausea. Vomiting.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media	Dry chemical. Carbon Dioxide (CO ₂). Alcohol-resistant foam. Water spray.
Unsuitable extinguishing media	High volume water jet.
Specific hazards arising from the chemical	Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Container may rupture on heating.
Specific protective equipment and precautions for firefighters	Wear self-contained breathing apparatus and full protective clothing for firefighting.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures	Keep unnecessary personnel away. Prevent further leakage or spillage if safe to do so. Use personal protective equipment. Use only non-sparkling tools.
Environmental precautions	Prevent the material from entering drains or water courses.
Methods and materials for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations.

7. HANDLING AND STORAGE

Precautions for safe handling	Avoid breathing vapor and contact with eyes, skin, and clothing. Do not leave containers open. Avoid repeated or prolonged contact with skin.
Conditions for safe storage, including any incompatibilities	Keep away from heat or flames. Keep in cool, dry, ventilated storage and in closed containers. Store away from oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters	<p><u>Calcium carbonate</u> OSHA</p> <p>PEL-TWA 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction)⁴⁶</p> <p>Skin notification N⁴⁶</p> <p>NIOSH</p> <p>REL-TWA 10 mg/m³ (total dust), 5 mg/m³ (respirable fraction)⁴⁶</p> <p>Skin notification N⁴⁶</p> <p>ACGIH</p> <p>TLV-TWA Withdrawn [2007] - Insufficient data.⁴⁶</p> <p>Skin notification NA⁴⁶</p> <p>CAL/OSHA</p> <p>PEL-TWA 10 mg/m³ (total dust), 5 mg/m³ (respirable fraction)⁴⁶</p> <p>Skin notification N⁴⁶</p> <p><u>Talcum powder</u> OSHA</p> <p>PEL-TWA 20 mppcf²⁰</p> <p>Skin notification N</p> <p>NIOSH</p> <p>REL-TWA 2 mg/m³ (resp)</p> <p>Skin notification N</p> <p>ACGIH</p> <p>TLV-TWA 2 mg/m³ (respirable particulate matter) [2009]</p> <p>Skin notification N</p> <p>CAL/OSHA</p> <p>PEL-TWA 2 mg/m³ (respirable dust)</p> <p>Skin notification N</p> <p><u>Unsaturated polyester resin</u> <u>styrene</u> OSHA</p> <p>PEL-TWA 100 ppm⁴⁷</p> <p>PEL-C 200 ppm; 600 ppm (Peak) for a single time period up to 5 min in any 3 hours</p> <p>Skin notification N</p> <p>NIOSH</p> <p>REL-TWA 50 ppm (215 mg/m³)</p> <p>REL-STEL 100 ppm (425 mg/m³)</p> <p>Skin notification N</p> <p>ACGIH</p> <p>TLV-TWA 20 ppm [1996]</p> <p>TLV-STEL 40 ppm [1996]</p> <p>Skin notification N</p> <p>CAL/OSHA</p> <p>PEL-TWA 50 ppm (215 mg/m³)</p> <p>PEL-STEL 100 ppm (425 mg/m³)</p> <p>PEL-C 500 ppm</p> <p>Skin notification Y</p> <p><u>Others</u></p>
Appropriate engineering controls	Provide adequate ventilation. Install local exhaust.
Personal protective equipment	
Respiratory protection	Organic vapor respirator
Hand protection	Rubber gloves. Neoprene.
Eye protection	Safety goggle.
Skin and body protection	Wear suitable clothing


9. PHYSICAL AND CHEMICAL PROPERTIES	
Appearance	High viscosity liquid paint
Odor	Aromatic like
Odor threshold	Not Available
pH	Not Available
Melting point/freezing point	Not Available
Initial boiling point and boiling range	Not Available
Flash point	>25
Evaporation rate	Not Available
Flammability (solid, gas)	Not available
Upper/lower flammability or explosive limits	Not available Not available
Vapor pressure	Not Available
Vapor density	Not Available
Relative density	1.75 - 1.85 g/cm3
Solubility(ies)	Slightly soluble in Aromatic solvent
Partition coefficient n-Octanol-water	Not Available
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
Viscosity	125 - 128 KU at 30 C

10. STABILITY AND REACTIVITY	
Reactivity	Reacts violently with strong acids and strong oxidants
Chemical stability	Stable under normal storage and handling conditions
Possibility of hazardous reaction	Will not occur
Condition to avoid	High temperatures, sparks, open flame, and all other sources of ignition
Incompatible materials	Strong oxidizing agents, strong acids
Hazardous decomposition products	Not available

11. TOXICOLOGICAL INFORMATION	
Acute toxicity (oral)	ATEmix = 5911.43 mg/kg (Not classified) Calcium carbonate LD50 (rat) oral = 6450.00 mg/kg ⁴³ styrene LD50 (rat) oral = 5000.00 mg/kg ⁴⁴
Acute toxicity (dermal)	Not available
Acute toxicity (dermal)	Not available
Skin corrosion and skin irritation	Causes skin irritation (styrene)
Serious eye damage or eye irritation	Causes serious eye irritation (styrene)
Respirator and skin sensitization	Not classified
Skin sentization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Suspected of damaging fertility or the unborn child (styrene)
Specific target organ toxicity following single exposure	Not classified
Specific target organ toxicity following repeated exposure	Causes damage to organs through prolonged or repeated exposure (styrene)
Aspiration hazard	Not classified

12. ECOLOGICAL INFORMATION	
Acute aquatic hazard	<p>Very toxic to aquatic life</p> <p><u>Calcium carbonate</u> ErC-EC72 (Fungi) 96 hr = 14 mg/L^{undefined}</p> <p><u>Talcum powder</u> LC50 (fish) 96 hr = 0.089 mg/L¹¹</p> <p>EC48 (shrimp) 48 hr = 0.00368 mg/L</p> <p>ErC-EC72 (Fungi) 96 hr = 0.007203 mg/L</p> <p><u>styrene</u> LC50 (fish) 96 hr = 9.1 mg/L</p> <p>EC48 (shrimp) 48 hr = 4.7 mg/L</p> <p>ErC-EC72 (Fungi) 96 hr = 0.72 mg/L</p>
Long term aquatic hazard	No information
Persistence and degradability	Rapidly degradable (styrene)
Bioaccumulative potential	<p>Bioaccumulative potential</p> <p><u>styrene</u> log KOW = 2.95</p> <p>BCF = 12-140</p>
Mobility in soil	The product is insoluble in water. If released to water, some of the components will have tendency to evaporate while other components are expected to be highly mobile in soil and have the potential to reach underground water supplies.
Other adverse effects	Not available

13. DISPOSAL CONSIDERATIONS	
Disposal methods	Disposing of this material/container should be done under all the regulations or handled by authorized waste collector in your country
Container disposal	Do not re-use empty containers

14. TRANSPORT INFORMATION	
Labels required	
UN number	1263
UN proper shipping name	Paint
Transport hazard class(es)	3
Packing group	III
Environmental hazards	Not applicable
Special precautions	Not applicable
Transport in bulk	Not applicable

15. REGULATORY INFORMATION	
Inventory of existing chemical substance produced or imported in USA (TSCA)	All component in this product are listed
Toxic substance control act (TSCA)	All component in this product are listed

16. OTHER INFORMATION	
Issue date: 26 August 2022	
References	
1. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~m8awRK:3 (3-5-19)	
2. https://echa.europa.eu/brief-profile/-/briefprofile/100.000.602 (23-12-19)	
3. https://echa.europa.eu/brief-profile/-/briefprofile/100.004.236#ScientificProperties (17-12-19)	

4. https://echa.europa.eu/brief-profile/-/briefprofile/100.000.599 (17-12-19)
5. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~Q1zAvm:3 (3-5-19)
6. https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/682 (04-05-19)
7. https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124 (24-12-19)
8. https://echa.europa.eu/brief-profile/-/briefprofile/100.004.236 (04-05-19)
9. https://echa.europa.eu/brief-profile/-/briefprofile/100.000.599 (3-5-19)
10. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~7TG1XJ:1 (03-05-19)
11. https://echa.europa.eu/brief-profile/-/briefprofile/100.035.328 (7/8/19)
12. https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/682 (04-05-19)
13. https://echa.europa.eu/brief-profile/-/briefprofile/100.014.124 (04-05-19)
14. https://echa.europa.eu/brief-profile/-/briefprofile/100.033.327 (3-5-19)
15. https://echa.europa.eu/brief-profile/-/briefprofile/100.033.327 (3-5-19)
16. https://www.osha.gov/chemicaldata/chemResult.html?recNo=122 (3-5-19)
17. https://www.osha.gov/chemicaldata/chemResult.html?recNo=476 (23-12-19)
18. www.oshahttps://www.osha.gov/chemicaldata/chemResult.html?recNo=178 (17-12-19)a.gov
19. https://www.osha.gov/chemicaldata/chemResult.html?recNo=474 (3-5-19)
20. https://www.osha.gov/chemicaldata/chemResult.html?recNo=277 (7/8/19)
21. https://www.osha.gov/chemicaldata/chemResult.html?recNo=246 (3-5-19)
22. https://www.osha.gov/chemicaldata/chemResult.html?recNo=228 (04-05-19)
23. https://www.osha.gov/chemicaldata/chemResult.html?recNo=178 (17-12-19)
24. https://pubchem.ncbi.nlm.nih.gov/compound/8095#section=Environmental-Fate-Exposure-Summary (03-05-19)
25. https://pubchem.ncbi.nlm.nih.gov/compound/180 (23-12-19)
26. https://pubchem.ncbi.nlm.nih.gov/compound/31272#section=Environmental-Abiotic-Degradation (04-05-19)
27. https://pubchem.ncbi.nlm.nih.gov/compound/887#section=Environmental-Fate-Exposure-Summary (3-5-19)
28. https://pubchem.ncbi.nlm.nih.gov/compound/7929#section=Environmental-Fate (04-05-19)
29. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~pB0xAg:1 (3-5-19)
30. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~VMFBml:3 (3-5-19)
31. https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/view/6025 (9-5-19)
32. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.297 (3-5-19)
33. https://echa.europa.eu/brief-profile/-/briefprofile/100.000.683 (3-5-19)
34. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.297
35. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~lQhZ8l:1 (03-05-19)
36. https://echa.europa.eu/brief-profile/-/briefprofile/100.155.514 (9-5-19)
37. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.297 (03-05-19)
38. https://www.osha.gov/chemicaldata/chemResult.html?recNo=490 (3-5-19)
39. https://www.osha.gov/chemicaldata/chemResult.html?recNo=89 (03-05-19)
40. https://www.osha.gov/chemicaldata/chemResult.html?recNo=808 (9-5-19)
41. https://pubchem.ncbi.nlm.nih.gov/compound/263#section=Octanol-Water-Partition-Coefficient (3-5-19)
42. https://pubchem.ncbi.nlm.nih.gov/compound/1140#section=Environmental-Fate (03-05-19)
43. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~tL93nR:1 (3-5-19)
44. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~lu5BAV:1 (03-05-19)
45. https://echa.europa.eu/brief-profile/-/briefprofile/100.006.765 (3-5-19)
46. https://www.osha.gov/chemicaldata/chemResult.html?recNo=220 (3-5-19)
47. https://www.osha.gov/chemicaldata/chemResult.html?recNo=14 (7/8/19)