

| 1. IDENTIFICATION OF THE MIXTURE AND OF THE SUPPLIER | |
|--|---|
| Product Identifier | |
| Product | Thinner 3A [86-100] |
| Recommended use of chemical | Use as Thinner for coatings |
| Restriction on use | No open flames, No spraks, and No smoking |
| Supplier's details | |
| Company | Big-Ben (Paints) Company Limited |
| Address | 38 Mu 7 Suanluangruamjai Road Suanluang Krathumban Samutsakorn 74110 Thailand |
| Telephone number | +66 2 811 1442 or +66 2 811 1443 |
| Fax number | +66 2 811 0632 |
| E-mail | bbp@bbp.co.th |
| Emergency phone number | +66 2 811 1442 or + 66 2 811 1443 |

| 2. HAZARD IDENTIFICATION | |
|---|------------|
| Classification of the substance or mixture | |
| This product has been classified in accordance with the hazard communication standard 29 CSR 1910.1200; the SDS and labels contain all the information as required by the standard. | |
| Flammable liquids | Category 1 |
| Acute toxicity - oral | Category 5 |
| Acute toxicity - dermal | Category 2 |
| Skin corrosion/irritation | Category 2 |
| Eye damage/irritation | Category 1 |
| Toxic to reproduction | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Aspiration hazard | Category 1 |
| Hazardous to the aquatic environment - acute hazard | Category 2 |
| Remark: | |
| Percentage of mixture consisting of ingredient(s) of unknown oral toxicity: 0.00% | |
| Percentage of mixture consisting of ingredient(s) of unknown dermal toxicity: 6.08% | |
| Percentage of mixture consisting of ingredient(s) of unknown inhalation toxicity: 78.44% | |

| GHS label elements | |
|---------------------|--|
| Pictogram or symbol |  |
| Signal word | Danger |

| | |
|--|--|
| Hazard statement: | |
| H224 Extremely flammable liquid and vapour | |
| H303 May be harmful if swallowed | |
| H304 May be fatal if swallowed and enters airways | |
| H310 Fatal in contact with skin | |
| H315 Causes skin irritation | |
| H318 Causes serious eye damage | |
| H335 May cause respiratory irritation | |
| H336 May cause drowsiness or dizziness | |
| H361 Suspected of damaging fertility or the unborn child | |
| H373 May cause damage to organs through prolonged or repeated exposure | |
| H401 Toxic to aquatic life | |
| Precautionary statement | |
| [PREVENTION] | |

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / lighting / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust / fume / gas / mist / vapors / spray.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

[RESPONSE]

P301+P310 IF SWALLOWED Immediately call a POISON CENTER or doctor / physician.

P302+P350 IF ON SKIN Gently wash with plenty of soap and water.

P302+P352 IF ON SKIN Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair) Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+P340 IF INHALED Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned Get medical advice / attention.

P310 Immediately call a POISON CENTER or doctor / physician.

P312 Call a POISON CENTER or doctor / physician if you feel unwell.

P314 Get medical advice / attention if you feel unwell.

P321 Specific treatment (see on this label).

P322 Specific measures (see on this label).

P331 Do NOT induce vomiting.

P332+P313 IF skin irritation occurs Get medical advice / attention.

P361 Remove / Take off immediately all contaminated clothing.

P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire Use dry sand, dry chemical or alcohol-resistant foam for extinction.

[STORAGE]

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

[DISPOSAL]

P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

| Chemical name | CAS No. | Content % (w/w) |
|--|----------|-----------------|
| 2-BUTOXYETHANOL | 111-76-2 | 3.18 - 5.93 |
| 2-Methylpropanol-1;2-Methylpropyl alcohol | 78-83-1 | 4.01 - 9.20 |
| Acetone | 67-64-1 | 5.48 - 16.78 |
| Butyl Acetate | 123-86-4 | 5.55 - 14.86 |
| Toluene | 108-88-3 | 40.77 - 91.69 |

| 4. FIRST AND MEASURES | |
|--|--|
| Inhalation | Remove to fresh air. If unconscious, place in recovery position and seek medical attention immediately. |
| Skin contact | Immediately flush with water for at least 15 minutes. Remove contaminated clothing. Seek medical attention immediately. Wash thoroughly after handling. |
| Eye contact | Hold eyelids apart and immediately flush with plenty of water for 15 minutes. Seek medical advice. Remove contact lenses. |
| Ingestion | Rinse mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. |
| Most important symptoms/effects, acute and delayed | Dizziness. Drowsiness. Headache. Nausea. Vomiting. Weakness. Unconsciousness. Skin and eye redness. Pain. Nausea. Vomiting. |

| 5. FIRE FIGHTING MEASURES | |
|--|--|
| Suitable extinguishing media | Dry chemical. Carbon Dioxide (CO ₂). Alcohol-resistant foam. Water spray. |
| Unsuitable extinguishing media | High volume water jet. |
| Specific hazards arising from the chemical | Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Container may rupture on heating. |
| Specific protective equipment and precautions for firefighters | Wear self-contained breathing apparatus and full protective clothing for firefighting. |

| 6. ACCIDENTAL RELEASE MEASURES | |
|--|--|
| Personal precautions, protective equipment, and emergency procedures | Keep unnecessary personnel away. Prevent further leakage or spillage if safe to do so. Use personal protective equipment. Use only non-sparkling tools. |
| Environmental precautions | Prevent the material from entering drains or water courses. |
| Methods and materials for containment and cleaning up | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations. |

| 7. HANDLING AND STORAGE | |
|--|---|
| Precautions for safe handling | Avoid breathing vapor and contact with eyes, skin, and clothing. Do not leave containers open. Avoid repeated or prolonged contact with skin. |
| Conditions for safe storage, including any incompatibilities | Keep away from heat or flames. Keep in cool, dry, ventilated storage and in closed containers. Store away from oxidizing agent. |


| 8. EXPOSURE CONTROLS/PERSONAL PROTECTION | |
|--|---|
| Control parameters | <p><u>2-BUTOXYETHANOL</u> OSHA</p> <p>PEL-TWA 50¹⁴ Skin notification Y¹⁴ NIOSH</p> <p>REL-TWA 5¹⁴ Skin notification Y¹⁴ ACGIH</p> <p>TLV-TWA 20¹⁴ Skin notification N¹⁴ CAL/OSHA</p> <p>PEL-TWA 20¹⁴ Skin notification Y¹⁴</p> <p><u>2-Methylpropanol-1;2-Methylpropyl alcohol</u> OSHA</p> <p>PEL-TWA 100¹⁵ Skin notification N¹⁵ NIOSH</p> <p>REL-TWA 50¹⁵ Skin notification N¹⁵ ACGIH</p> <p>Skin notification N¹⁵ CAL/OSHA</p> |

| | |
|--------------------------------------|---|
| | <p>Skin notification N¹⁵</p> <p><u>Acetone</u> OSHA</p> <p>PEL-TWA 1000¹⁶</p> <p>Skin notification N¹⁶ NIOSH</p> <p>REL-TWA 250¹⁶</p> <p>Skin notification N¹⁶ ACGIH</p> <p>TLV-TWA 2500¹⁶</p> <p>TLV-STEL 500¹⁶</p> <p>Skin notification N¹⁶ CAL/OSHA</p> <p>PEL-TWA 500¹⁶</p> <p>PEL-STEL 750¹⁶</p> <p>PEL-C 3000¹⁶</p> <p>Skin notification N¹⁶</p> <p><u>Butyl Acetate</u> OSHA</p> <p>PEL-TWA 150¹⁷</p> <p>Skin notification N¹⁹ NIOSH</p> <p>REL-TWA 150¹⁹</p> <p>REL-STEL 200¹⁹</p> <p>Skin notification N¹⁹ ACGIH</p> <p>TLV-TWA 50¹⁹</p> <p>TLV-STEL 150¹⁹</p> <p>Skin notification N CAL/OSHA</p> <p>PEL-TWA 150¹⁹</p> <p>PEL-STEL 200¹⁹</p> <p>Skin notification N¹⁹</p> <p><u>Toluene</u> OSHA</p> <p>PEL-TWA 200 ppm¹⁸</p> <p>PEL-C 300 ppm; 500 ppm (Peak) [10 min maximum in an 8 hr shift]¹⁸</p> <p>Skin notification N¹⁸ NIOSH</p> <p>REL-TWA 100 ppm (375 mg/m³)¹⁸</p> <p>REL-STEL 150 ppm (560 mg/m³)¹⁸</p> <p>Skin notification N¹⁸ ACGIH</p> <p>TLV-TWA 20 ppm [2006]¹⁸</p> <p>Skin notification N¹⁸ CAL/OSHA</p> <p>PEL-TWA 10 ppm (37 mg/m³)¹⁸</p> <p>PEL-STEL 150 ppm (560 mg/m³)¹⁸</p> <p>PEL-C 500 ppm¹⁸</p> <p>Skin notification Y¹⁸</p> |
| Appropriate engineering controls | Provide adequate ventilation. Install local exhaust. |
| Personal protective equipment | |
| Respiratory protection | Organic vapor respirator |
| Hand protection | Rubber gloves. Neoprene. |
| Eye protection | Safety goggle. |
| Skin and body protection | Wear suitable clothing |

| 9. PHYSICAL AND CHEMICAL PROPERTIES | |
|--|--|
| Appearance | Liquid Clear |
| Odor | Organic solvent |
| Odor threshold | Not Available |
| pH | Not Available |
| Melting point/freezing point | Not Available |
| Initial boiling point and boiling range | Not Available |
| Flash point | lower than 23 |
| Evaporation rate | Not Available |
| Flammability (solid, gas) | Not Available |
| Upper/lower flammability or explosive limits | Not available Not available |
| Vapor pressure | Not Available |
| Vapor density | Not Available |
| Relative density | 0.83 - 0.85 |
| Solubility(ies) | Soluble in Organic solvent |
| Partition coefficient n-Octanol-water | Not Available |
| Auto-ignition temperature | Not Available |
| Decomposition temperature | Not Available |
| Viscosity | 11-12 second by Ford cup No.4 |
| 10. STABILITY AND REACTIVITY | |
| Reactivity | Reacts violently with strong acids and strong oxidants |
| Chemical stability | Stable under normal storage and handling conditions |
| Possibility of hazardous reaction | Will not occur |
| Condition to avoid | High temperatures, sparks, open flame, and all other sources of ignition |
| Incompatible materials | Strong oxidizing agents, strong acids |
| Hazardous decomposition products | Not available |

| 11. TOXICOLOGICAL INFORMATION | |
|--|--|
| Acute toxicity (oral) | <p>ATEmix = 3383.28 mg/kg (Category 5)</p> <p>2-BUTOXYETHANOL LD50 (rat) oral = 470.00 mg/kg¹</p> <p>2-Methylpropanol-1;2-Methylpropyl alcoho LD50 (rat) oral = 2460.00 mg/kg²</p> <p>Acetone LD50 (rat) oral = 5800.00 mg/kg³</p> <p>Butyl Acetate LD50 (rat) oral = 10736.00 mg/kg⁴</p> <p>Toluene LD50 (rat) oral = 5000.00 mg/kg⁵</p> |
| Acute toxicity (dermal) | <p>ATEmix = 165.58 mg/kg (Classify 2)</p> <p>2-BUTOXYETHANOL LD50 (rabbit) dermal = 400.00 mg/kg¹</p> <p>Acetone LD50 (rabbit) dermal = 7426.00 mg/kg³</p> <p>Butyl Acetate LD50 (rabbit) dermal = 16.00 mg/kg⁴</p> <p>Toluene LD50 (rabbit) dermal = 14100.00 mg/kg⁵</p> |
| Acute toxicity (dermal) | <p>ATEmix = 124.50 mg/kg (Not classified)</p> <p>Acetone LC50 (rat) inhalation = 76.00 mg/kg³</p> <p>Butyl Acetate LC50 (rat) inhalation = 740.00 mg/kg⁴</p> |
| Skin corrosion and skin irritation | Causes skin irritation (2-BUTOXYETHANOL,2-Methylpropanol-1;2-Methylpropyl alcoho,Toluene) |
| Serious eye damage or eye irritation | Causes serious eye damage (2-BUTOXYETHANOL,2-Methylpropanol-1;2-Methylpropyl alcoho,Acetone) |
| Respirator and skin sensitization | Not classified |
| Skin sentization | Not classified |
| Germ cell mutagenicity | Not classified |
| Carcinogenicity | Not classified |
| Reproductive toxicity | Suspected of damaging fertility or the unborn child (Toluene) |
| Specific target organ toxicity following single exposure | May cause respiratory irritation (2-Methylpropanol-1;2-Methylpropyl alcoho,Acetone,Butyl Acetate,Toluene) |
| Specific target organ toxicity following repeated exposure | May cause damage to organs through prolonged or repeated exposure (Toluene) |
| Aspiration hazard | May be fatal if swallowed and enters airways (Toluene) |

| 12. ECOLOGICAL INFORMATION | |
|-------------------------------|---|
| Acute aquatic hazard | <p>Toxic to aquatic life</p> <p><u>2-BUTOXYETHANOL</u> LC50 (fish) 96 hr = 1474 mg/L¹¹</p> <p>EC48 (shrimp) 48 hr = 1500 mg/L¹¹</p> <p><u>2-Methylpropanol-1;2-Methylpropyl alcoho</u> LC50 (fish) 96 hr = 1430 mg/L⁷</p> <p>EC48 (shrimp) 48 hr = 1100 mg/L⁷</p> <p>ErC-EC72 (Fungi) 96 hr = 593 mg/L⁷</p> <p><u>Acetone</u> LC50 (fish) 96 hr = 4740 mg/L³</p> <p><u>Butyl Acetate</u> LC50 (fish) 96 hr = 18 mg/L⁴</p> <p>EC48 (shrimp) 48 hr = 32 mg/L⁴</p> <p><u>Toluene</u> LC50 (fish) 96 hr = 7.3 mg/L¹²</p> <p>EC48 (shrimp) 48 hr = 6 mg/L¹²</p> <p>ErC-EC72 (Fungi) 96 hr = 12.5 mg/L¹²</p> |
| Long term aquatic hazard | No information |
| Persistence and degradability | Rapidly degradable (2-Methylpropanol-1;2-Methylpropyl alcoho,Acetone,Butyl Acetate,Toluene) |
| Bioaccumulative potential | <p>Bioaccumulative potential</p> <p><u>2-BUTOXYETHANOL</u> log KOW = 0.83²⁰</p> <p>BCF = 3²⁰</p> <p><u>2-Methylpropanol-1;2-Methylpropyl alcoho</u> log KOW = 0.76²¹</p> <p>BCF = 3²¹</p> <p><u>Acetone</u> log KOW = -0.24²²</p> <p>BCF = 0.69²²</p> <p><u>Butyl Acetate</u> log KOW = 1.78²³</p> <p>BCF = 7.00²³</p> <p><u>Toluene</u> log KOW = 2.73²⁴</p> <p>BCF = 13²⁴</p> |
| Mobility in soil | The product is insoluable in water. If released to water, some of the components will have tendency to evaporate while other components are expected to be highly mobile in soil and have the potential to reach underground water supplies. |
| Other adverse effects | Not available |
| 13. DISPOSAL CONSIDERATIONS | |
| Disposal methods | Disposing of this material/container should be done under all the regulations or handled by authorized waste collector in your country |
| Container disposal | Do not re-use empty containers |

| 14. TRANSPORT INFORMATION | |
|---|--|
| Labels required |  |
| UN number | 1263 |
| UN proper shipping name | Paint |
| Transport hazard class(es) | 3 |
| Packing group | III |
| Environmental hazards | Not applicable |
| Special precautions | Not applicable |
| Transport in bulk | Not applicable |
| 15. REGULATORY INFORMATION | |
| Inventory of existing chemical substance produced or imported in USA (TSCA) | All component in this product are listed |
| Toxic substance control act (TSCA) | All component in this product are listed |
| 16. OTHER INFORMATION | |
| Issue date: 17 August 2022 | |
| References | |
| 1. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~IQIQFd:1 (03-05-19) | |
| 2. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~9YNeeY:1 (11-7-19) | |
| 3. https://echa.europa.eu/brief-profile/-/briefprofile/100.000.602 (23-12-19) | |
| 4. https://echa.europa.eu/brief-profile/-/briefprofile/100.004.236#ScientificProperties (17-12-19) | |
| 5. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~VMFBml:3 (3-5-19) | |
| 6. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.550 (03-05-19) | |
| 7. https://echa.europa.eu/brief-profile/-/briefprofile/100.001.044 (11-7-19) | |
| 8. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.297 (3-5-19) | |
| 9. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.297 | |
| 10. https://echa.europa.eu/brief-profile/-/briefprofile/100.004.236 (04-05-19) | |
| 11. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.550#ScientificProperties (17-12-19) | |
| 12. https://toxnet.nlm.nih.gov/cgi-bin/sis/search2/f?./temp/~lQhZ8l:1 (03-05-19) | |
| 13. https://echa.europa.eu/brief-profile/-/briefprofile/100.003.297 (03-05-19) | |
| 14. https://www.osha.gov/chemicaldata/chemResult.html?recNo=130 (03-05-19) | |
| 15. https://www.osha.gov/chemicaldata/chemResult.html?recNo=676 (11-7-19) | |
| 16. https://www.osha.gov/chemicaldata/chemResult.html?recNo=476 (23-12-19) | |
| 17. https://www.osha.gov/chemicaldata/chemResult.html?recNo=178 (17-12-19)a.gov | |
| 18. https://www.osha.gov/chemicaldata/chemResult.html?recNo=89 (03-05-19) | |
| 19. https://www.osha.gov/chemicaldata/chemResult.html?recNo=178 (17-12-19) | |
| 20. https://pubchem.ncbi.nlm.nih.gov/compound/8133#section=Environmental-Abiotic-Degradation (03-05-19) | |
| 21. https://pubchem.ncbi.nlm.nih.gov/compound/6560#section=Octanol-Water-Partition-Coefficient (11-7-19) | |
| 22. https://pubchem.ncbi.nlm.nih.gov/compound/180 (23-12-19) | |
| 23. https://pubchem.ncbi.nlm.nih.gov/compound/31272#section=Environmental-Abiotic-Degradation (04-05-19) | |
| 24. https://pubchem.ncbi.nlm.nih.gov/compound/1140#section=Environmental-Fate (03-05-19) | |