# 21-41



## HARDENER for 2K primer 4:1

**BIC-BEN® HARDENER** 

VERSION	Physical Properties		
Version 1	Supply viscosity	8-12 sec by Ford cup No.4 at 30 <sup>o</sup> C	
Date 20 December 2019	Specific gravity	0.91-1.01 g/cm <sup>3</sup>	
	Shelf life	1 Year	
		Store in average temperature between 40 – 95 °F (5 – 35 °C). Avoid too much temperature fluctuation or direct contact with sunlight. Suitable storage	

temperature is 70 °F or 21°C

#### **PRODUCT DESCRIPTION**

21-Line, Isocyanate for polyurethane paint system. It's provide good, reactivity with Acrylic polyol paint system. It's also provide good appearance, high gloss, good weathering resistance, after completed reaction.

#### **APPLICATION PARAMETERS**

Mixing ratio	Part A : Hardener : Thinner		
	4: 1 : 5-15% By Volume		
	Please see in Part A information.		
Part A	80-Line		
Reducer Thinner	2K Thinner # 86-120		
Spray viscosity	Ford cup No. 4	15-20 seconds	
Pot life	2– 3 hr. at 25 <sup>o</sup> C		
Spray condition	Gravity feed	1.2 – 1.4 mm	
	Air pressure	1.7 -2.2 bar	
		28 – 30 psi	
		HVLP max 0.6 – 0.7 bar (8-10 psi) at the air cap	
Number of coats	2 coats	Dry film thickness 60-80 micron.	

### **KEY CHARACTERISTICS**

- Isocyanate
- Part B for Polyurethane paint system
- Good weathering clear coat

PRECAUTION	
Warning	For professional or trained applicator use only. Not for sale or use by the general public. before use, read and follow all TDS, label, and SDS precautions. Flammable product. Keep out reach of children. Always wear approved organic vapor goggle and safety mask when using product. Apply paint in good ventilating area.

This product data sheet is intended to describe Big-Ben's product application. It should not be therefore be constructed as guarantee in any specific property of the product. We assume no liability in connection with its use.