

PRODUCT DATA SHEET | ข้อมูลผลิตภัณฑ์



CLEAR COAT 4:1 BIC-BEN® 2K TOPCOAT

VERSION

Version 1

Date 5 November, 2020

PRODUCT DESCRIPTION

short time for film setting.

47-8051, 2K 4:1 Topcoat. It's providing high-gloss, Good hardness. Excellent in weathering resistance. It's design for large area. It's provide long pot life but

PHYSICAL PROPERTIES

Supply viscosity	15 – 17 second by ford cup No.4	
Specific gravity	0.88 – 0.98 g/cm ³	
Degree of gloss	Min 80 GU at 60 ^o	
Shelf life	1 Year Store in average temperature between 40 $-$ 95 °F (5 $-$ 35 °C). Avoid too much temperature fluctuation or direct contact with sunlight. Suitable storage temperature is 70 °F or 21 °C	
Product code	Gallon #47-8051L	

APPLICATION PARAMETERS

71 FECATION FARAMETERS				
	Part A: Hardener: Thinner 4:1:1 By Volume			
Mixing ratio				
Hardener	Hardener for 2K Top Coat RGB 4:1 #21-51			
Reducer Thinner	2K Thinner # 86-120			
Coverage	10 m ² / Gallon ready to use mixture at dry film 50 micron			
	By using the recommended application, the theoretical material coverage Note. The practice material usage depends on many factors i.e. shape of object, roughness of the surface, application techniques, pressure and application circumstances.			
\[\s\ \]s	Ford cup No. 4 15-18 seconds			
Spray viscosity				
	2– 3 hr. at 25 °C			

KEY CHARACTERISTICS

- RGB 4:1 clearcoat
- High-gloss and hardness
- Good weathering clear coat

≱11	Gravity feed	1.2 – 1.4 mm	1	
	Air pressure	1.7 -2.2 bar		
/ L		28 – 30 psi		
Spray condition		HVLP max $0.6 - 0.7$ bar (8-10 psi) at the air cap		
7	2 coats	Dry film thick	kness 50-60 micro	n.
lumber of coats				
<mark>}↑}↑</mark>	10 – 15 mins	at 25 – 30 °C		
		20 °C	30 °C	40 °C
(~~-)	Dust free time	30 min	20 mins	10 mins
<u> </u>	Dry to handle	9-10 hr.	7-8 hr.	4-5 hr.
Dry time	Dry to polish	9-10 hr.	7-8 hr.	4-5 hr.

PRECAUTION

Warning	For professional or trained applicator use only. Not for sale or use by the general public. before use, read and follow all TDS, label, and SDS precautions. Flammable product. Keep out
	reach of children. Always wear approved organic vapor goggle and safety mask when using product. Apply paint in good ventilating area.