

55-8002

Acrylic Matting Agent

BIC-BEN® BASECOAT

VERSION

Version 1
Date 4 February, 2020

PHYSICAL PROPERTIES

| | |
|------------------|--|
| Supply viscosity | 55 - 61 KU at 30 °C |
| Specific gravity | 0.90 – 1.00 g/cm ³ |
| Gloss | 5 Gloss Unit at 60 °C [Fully matt] |
| Shelf life | 1 Year Store in average temperature between 40 – 95 °F (5 – 35 °C). Avoid too much temperature fluctuation or direct contact with sunlight. Suitable storage temperature is 70 °F or 21°C |

PRODUCT DESCRIPTION

55-8002 is matting additive. It's provided for gloss adjustment in automotive paint. Its designed for good compatibility with wide range of paint system and easy to use.

APPLICATION PARAMETERS

| | |
|-----------------|---|
| Mixing ratio | Basecoat paint : 55-8002 100 : 10 – 60% by Volume |
| Reducer Thinner | Standard Thinner-Premium # 86-100 Standard Thinner-Economic #86-158 Follow Basecoat instruction |

KEY CHARACTERISTICS

- Matting additive
- 1K Acrylic paint
- Paint for automotive
- High performance additive
- Good weathering basecoat

PRECAUTION

| | |
|---------|---|
| Warning | For professional or trained applicator use only. Not for sale or use by the general public. before use, read and follow all TDS, label, and SDS precautions. Flammable product. Keep out reach of children. Always wear approved organic vapor goggle and safety mask when using product. Apply paint in good ventilating area. |
|---------|---|

This product data sheet is intended to describe Big-Ben's product application. It should not be therefore be constructed as guarantee in any specific property of the product. We assume no liability in connection with its use.