

83-4335

LIGHT WEIGHT POLYESTER PUTTY WITH HARDENER (LIGHT PINK)

Two component Putty I Pink putty

VERSION

Version 1

Date 10 January, 2020

PRODUCT DESCRIPTION

83-4335, is two component Pink Putty that use as body filler for small and large dent area. It provides excellent adhesion to all metals. In addition, it can be apply direct to metal or on primer. It's can used as heavy build filler without affecting the gloss of top/base coat.

SUITABLE SUBSTRATE

Direct to steel
 Direct to Aluminum
 Direct to galvanized steel
 OEM Electro coat [E-coat]
 Existing finishes
 Glass Reinforce Polyester laminates
 Polyester Body filler

KEY CHARACTERISTICS

- Quick dry
- Primer or sealer
- Easy to sanding
- Can be tinted with Universal Mixing System #600-xxx

PHYSICAL PROPERTIES

Color	Light Pink
Supply viscosity	125 – 130 KU at 30 °C Remark: 83-4335 : Styrene monomer 100:10 for viscosity check
Specific gravity	1.60 – 1.70 g/cm ³
Gel time	3 – 4 minutes
Shelf Life	6 months, Store in average temperature between 40 – 95 °F (5 – 35 °C). Avoid too much temperature fluctuation or direct contact with sunlight. Suitable storage temperature is 70 °F or 21°C

MIXING AND RELATED PRODUCTS

Mixing Ratio	Paint : Hardener [100 : 3] [by Volume]
Hardener	Hardener for 2K Putty # 21-67 [Yellow Hardener] or recommended by our technician
Sanding time	30 – 45 minutes.

PRECAUTION

Warning	For professional or trained applicator use only. Not for sale or use by the general public. Before use, read and follow all TDS, label, and SDS precautions. Flammable product. Keep outreach of children. Always wear approved organic vapor goggle and safety mask when using product. Apply paint in good ventilating area.
---------	--

This product data sheet is intended to describe Big-Ben's product application. It should not be therefore be constructed as guarantee in any specific property of the product. We assume no liability in connection with its use.