



85-31

Thinner for 59-Line

BIC-BEN® THINNER

VERSION

Version 1
Date 20 December 2019

PHYSICAL PROPERTIES

| | |
|------------------|--|
| Appearance | Clear by visual |
| Specific gravity | 0.79 – 0.81 g/cm ³ |
| Shelf life | 1 Year Store in average temperature between 40 – 95 °F (5 – 35 °C). Avoid too much temperature fluctuation or direct contact with sunlight. Suitable storage temperature is 70 °F or 21°C |
| Product Code | Gallon#85-31L |

PRODUCT DESCRIPTION

85-31, is Thinner for Alkyd Enamel paint dilution. It's suitable for paint dilution. Its good excellent for reduce paint viscosity for spray. it's provide smooth dry film of paint.

APPLICATION PARAMETERS

| | |
|-----------------|------------------------------------|
| Mixing ratio | Follow main product recommendation |
| Spray viscosity | Follow main product recommendation |
| Spray condition | Follow main product recommendation |
| Number of coats | Follow main product recommendation |
| Flash time | Follow main product recommendation |
| Dry time | Follow main product recommendation |

KEY CHARACTERISTICS

- Thinner
- thinner for automotive

PRECAUTION

| | |
|---------|---|
| Warning | For professional or trained applicator use only. Not for sale or use by the general public. before use, read and follow all TDS, label, and SDS precautions. Flammable product. Keep out reach of children. Always wear approved organic vapor goggle and safety mask when using product. Apply paint in good ventilating area. |
|---------|---|

This product data sheet is intended to describe Big-Ben's product application. It should not be therefore be constructed as guarantee in any specific property of the product. We assume no liability in connection with its use.